



### Size

The DU hospital pattern disposal unit without plain top has an overall plan size of 600 x 600 mm in accordance with the requirements of HTM64: Sanitary assemblies (2006).

### Disposal Hopper

The disposal hopper has full rim flushing to ensure efficient and hygienic cleansing.

### Waste Outlet

The disposal hopper is manufactured with a 110 mm o/d plain vertical spigot outlet.

A white polypropylene P or S trap can be supplied to convert the vertical spigot into a horizontal or vertical outlet.

### Flushing Inlet

The disposal hopper is supplied as standard with a concealed back entry flushpipe connection for a duct mounted cistern

As an option the hopper can be provided with an exposed top entry connection for a surface mounted cistern.

### Cistern and Flushpipe

As an option the disposal unit can be supplied with a concealed duct mounted plastic manual single flush 6-9 litre cistern with flushpipe and through wall operating mechanism for a concealed back entry connection. Alternatively for an exposed top entry connection an exposed surface mounted stainless steel manual single flush 6-9 litre cistern with flushpipe and front lever operating mechanism can be supplied. All cisterns are SISO and complete with lid, flush valve and float operated inlet valve.

### Cistern Height

To efficiently flush the hopper the recommended mounting height is 1450 mm minimum from the underside of the cistern to finished floor level.

### Product Code Selection for Order or Quotation

#### 1. Base Product Code

804 -Disposal Unit

#### 2. Disposal Hopper Flushpipe Connection

-TE -top entry       -BE -back entry

#### 3. Options

- P -white polypropylene P trap
- S -white polypropylene S trap
- 142 -plastic concealed manual cistern
- 132 -stainless steel manual cistern
- FL -front support legs
- BG -hinged bucket grid

