

Special Features

- ▲ HYGIENIC VANDAL RESISTANT DESIGN
- ▲ GLASS FILLER OPTION
- ▲ CHOICE OF SHROUD FINISHES

Description

The wall mounted water cooler is self-contained, vandal resistant, mains fed and provides 30.3 litres per hour of chilled water from 26.7°C to 10°C. The cooler is supplied as standard with a flexible non-squirt design bubbler valve activated by an internally mounted self closing push button valve. A glass filler may be provided in addition to the bubbler valve.

Construction

The top of the water cooler is manufactured from grade 304 stainless steel and incorporates an integral waste outlet. The shroud is manufactured from galvanised steel with a granite powder coated finish. As an option a stainless steel shroud manufactured from 304 grade stainless steel can be provided.

The evaporator is an insulated copper tube on a stainless steel tank. The refrigerant is R-134a and is capillary tube controlled.

Electrical Supply

The water cooler is supplied with a lead and plug for connection to a 13 amp socket

Certification

The water cooler complies with ANSI/NSF 61, section 9 and with the Air Conditioning and Refrigeration Institute Standard 1010.

Options

- ▲ Stainless Steel Shroud
- ▲ Granite effect coated steel shroud (illustrated)
- ▲ Glass Filler (in addition to bubbler valve)
- ▲ 115v / 60Hz compressor available (export models)

Order Codes and Technical Specification

Please refer to the Technical Specification Sheet

