

Special Features

- ▲ VANDAL RESISTANT DESIGN
- ▲ HEAVY GAUGE 1.5 mm THICK STAINLESS STEEL
- ▲ HYGIENIC ONE PIECE CONSTRUCTION
- ▲ EASILY AND QUICKLY INSTALLED
- ▲ FRONT SUPPORT LEGS FOR EXTRA STRENGTH
- ▲ COST EFFECTIVE COMPARED TO TRADITIONAL BASINS
- ▲ CHOICE OF OUTLET POSITIONS

Description

The wash trough is designed for heavy use and is ideal for locations where a number of users require washing facilities at the same time. Easy to install with only one waste outlet connection, the wash trough is often a more cost effective solution for multiple washing applications compared to several traditional basins.

The wash trough is available in a splashback model (code 301) for use with wall mounted water outlets or in a taplanding model (code 302) requiring deck mounted outlets. Both models are supplied with front support legs and are available in a range of standard and special lengths.

Construction

The wash trough is manufactured in one piece without joints or crevices from grade 304 stainless steel, with all exposed surfaces polished to a satin finish. Incorporated in the wash trough is a right hand or a left hand outlet and either an integral splashback or a tap landing with rear upstand.

Available in five standard lengths or special lengths, all wash troughs have wall mounting brackets and are provided with stainless steel front support legs. Each wash trough is supplied with an unslotted flush grated waste fitting.



Options

- ▲ Non-standard tap hole sizes (taplanding model only)
- ▲ Free standing island range framework to mount back to back wash troughs (taplanding model only).
- ▲ Water controllers, taps and valves

Order Codes and Technical Specification

Please refer to the Technical Specification Sheet

