



### Special Features

- ▲ FACTORY ASSEMBLED FOR EASY, LOW COST INSTALLATION
- ▲ SPACE SAVING DESIGN
- ▲ INDIVIDUAL TIMED FLOW VALVES FOR WATER ECONOMY
- ▲ GRADE 316 STAINLESS STEEL CONSTRUCTION
- ▲ 1, 2, 3 or 4 USER MODELS
- ▲ OPTIONAL FOOT SPRAYS

### Description

The product is specifically designed for installing near to beaches or swimming pools, providing bathers with showering facilities. The beach shower is free standing and is factory assembled with either two, three or four individual timed flow water control outlets which are pre-piped requiring only a single supply connection. Up to four optional foot sprays can also be provided.

### Construction

The beach shower is constructed from heavy gauge grade 316 stainless steel, with all exposed surfaces polished to a satin finish. Incorporated in the shower column is a heavy duty base mounting flange and a removable side access panel held in position by security type screws. The shower is supplied factory fitted with a fixed spray head and timed flow push button valve for each user together with a water supply manifold and all internal piping. Models are available to suit 1, 2, 3, or 4 users. A steel anchor plate, coated with a rust preventative, together with reinforcing bars provides a secure mounting for the shower.

### Operation

Each user has their own fixed spray head and push button timed flow valve which is adjustable to give between 5 and 60 seconds operation. The beach shower is designed to connect to a single pipe, from below supplying either cold or temperature controlled warm water. If the installation is subject to freezing then the installer should provide a water drain down facility.

### Order Codes and Technical Specification

Please refer to the Technical Specification Sheet