

## TECHNICAL DATA SHEET PROFLOOR ANTI-SLIP AGGREGATE COMPONENT

TDS: CVM1121  
135/M112/1

### DESCRIPTION:

Profloor Anti-Slip Aggregate Component ground mineral powder of specific particle size (0.25 – 0.39mm)

### RECOMMENDED USE:

Profloor Anti-Slip Aggregate Component to be used to create anti-slip element to Profloor finish.

### AVAILABILITY:

220g

### FINISH:

N/A

### COLOUR:

Neutral

### TYPICAL S.G. (SPECIFIC GRAVITY):

2.85 @ 20 °C

### VOLUME SOLIDS:

N/A

### WET FILM THICKNESS W.F.T

N/A

### DRY FILM THICKNESS D.F.T

N/A

### EXPECTED SPREADING RATE:

20 sq.m / can

To be scattered evenly.

The practical spreading rate may be lower as this depends on factors such as the porosity and roughness of the surface to be painted and material losses during application.

### TYPICAL VISCOSITY:

N/A

### FLASH POINT:

Non-flammable

### DRYING TIME: @ RECOMMENDED D.F.T

Touch dry: N/A

Hard dry: N/A

Full hardness: N/A

Low temperature and high humidity will adversely affect application, drying and performance of any coating.

### MINIMUM OVERCOATING TIME:

N/A

### APPLICATION SPECIAL CONDITIONS:

N/A

### VOC CONTENT:

N/A

VOC's (Volatile Organic Compounds) contribute to atmospheric pollution

### APPLICATION DETAILS:

Application restrictions N/A

Method: Scattering

Thinner (Max vol): N/A

Nozzle size: N/A

Nozzle pressure: N/A

Cleaning solvent: N/A

Recoat interval: N/A

### SURFACE PREPARATION:

N/A

For further advice contact Coo-Var Technical Services on +44(0)1482 328053

The physical constants are subject to normal manufacturing tolerances.

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

**PROFLOOR ANTI-SLIP AGGREGATE COMPONENT****135/M112/1**

---

**MIXING INSTRUCTIONS:**

N/A

**APPLICATION CONDITIONS:**

The product should be evenly scattered over the first coat of Coo-Var Profloor Floor Paint whilst the coat is still tacky. The second coat of profloor, when applied over the top of the cured first coat will seal the anti-slip aggregate in place.

**PRECEDING COAT:**

Coo-Var Profloor Floor Paint

**SUBSEQUENT COAT:**

Coo-Var Profloor Floor Paint

**REMARKS:****HEALTH AND SAFETY:**

See safety data sheet - SDS 10775

**ISSUED:**

08 August 2011

**REVISION:**

0

The information given in this data sheet is based on experience and is accurate to the best of our knowledge. No guarantee should be implied, however, as the conditions of use are beyond our control. This data sheet does not constitute a specification. In case of doubt as to the suitability of the product please contact our Technical Service Department on 01482 328053.

**For further advice contact Coo-Var Technical Services on +44(0)1482 328053**

**The physical constants are subject to normal manufacturing tolerances.**

**"COVERING OUR CUSTOMERS' NEEDS SINCE 1908"**

---

**Ellenshaw Works**

Lockwood Street, Hull HU2 0HN

Tel.: +44(0)1482 328053. Fax: +44(0)1482 219266

**COO-VAR**Email: [info@coo-var.co.uk](mailto:info@coo-var.co.uk)[www.coo-var.co.uk](http://www.coo-var.co.uk)