




White with optional sensor operated spouts



Grey with optional lever operated taps



Standard colours:
These colours are an indicative guide
only as colour rendition varies
between screens and printers

Special Features

- ▲ VANITY OR WALL MOUNTING OPTION
- ▲ INCLINE TROUGH LEADING TO DISCREET SLOT DRAIN
- ▲ SPLIT LEVEL DUAL HEIGHT OPTION TO INCLUDE DISABLED USERS AND CHILDREN
- ▲ TAPLANDING DESIGN
- ▲ EASY TO CLEAN AND MAINTAIN
- ▲ SMOOTH NON-POROUS HYGIENIC DESIGN
- ▲ WIDE CHOICE OF COLOURS
- ▲ CAN BE SUPPLIED WITH OPTIONAL SENSOR TAPS OR MECHANICAL TAPS

Description

The Rezina Incline solid surface slope lid wash trough features sloping internal surfaces leading to discreet slot drain and is ideally suited for use in schools, universities, nightclubs, bars, restaurants, office and hotel washrooms, where a modern aesthetically pleasing appearance is desired. The wash trough can be supplied in a choice of standard or special colours with a tap landing (for deck mounted outlets). The solid surface wash trough is designed for mounting to vanity units (by others) with the option for wall mounting if desired. A split level dual height option can be supplied to facilitate use by disabled users and children. The Rezina Incline trough is supplied in a range of standard and made-to-measure lengths.

Construction

The Incline wash trough is manufactured from a blend of acrylic resin, natural pigments and aluminium hydroxide to give a natural stone appearance. A two stage thermal curing process at high temperature gives the solid surface material superb strength and durability. The wash trough is formed with inclined inner surfaces leading to a discreet slotted drain with hidden waste outlet. Designed for deck mounting, or "sit-on" type installation onto an existing vanity unit type construction (by others). Optional metal brackets can be supplied for wall mounting the trough. Available in seven standard lengths, all solid surface wash troughs are supplied with an unslotted flush grated waste fitting and tap holes as required.

Sizes

Available in standard lengths: 600, 1200, 1800, 2400, 3000 and 3600 mm. Special order lengths can be supplied up to 3600 mm.

Options

- ▲ Special colours
- ▲ Metal wall mounting brackets
- ▲ Split level dual height to include use by disabled users and children
- ▲ "Non-Touch" sensor taps
- ▲ Mechanical taps

Order Codes and Technical Specification

Please refer to the Technical Specification Sheet