



The AUTOPA Square TOPLOK Parking Post

The AUTOPA Square TOPLOK Parking Post is a padlockable variant of the original hinged parking post. The tried and tested design ensures that your parking space will always be available when required. Highly durable, the parking post is manufactured from mild steel and is galvanised as standard to ensure its longevity.

The AUTOPA Square TOPLOK Parking Post is locked by fitting a padlock to the top of the post through the lower hole of the bar protruding through the top of the post. Supplied flanged only, colour coated versions are also available (please specify BS/RAL numbers at time of order).

Product Range

Order Code	Description	Weight
138 300 521	Galvanised	7.0kg
138 300 524	Galvanised & yellow	7.0kg

Accessories & installation parts

138 100 906	40mm Brass Padlock with 2 Keys (Random Key)
138 100 907	40mm Brass Padlock with 2 Keys (Identical Key)
138 100 991	M16 Expanding Bolt (2 required per post)

Product details

780mm x 100mm x 200mm (h x w x l)
60mm x 60mm square galvanised steel body
110mm minimum vehicle clearance


Installation & use

Each post requires bolting down to a suitable concrete surface (not less than 300mm³) by means of two 16mm anchor bolts. The area surrounding the installation must be flat and level with no nearby surface irregularities or gradient changes. Care must be taken to ensure the square base recess is kept clear of cement and any other debris during installation and use. This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103