



### **The AUTOPA RetractaPost-GL 745**

*The RetractaPost-GL offers a highly effective and robust way to protect premises and vehicles. The RetractaPost-GL is raised and lowered vertically and is 745mm tall when raised. When lowered the post is fully below ground and covered using the integral lid. The post is lockable in the raised position by rotating the post 45° and then pressing the high-security push button 7-pin security lock. The post is unlocked using the supplied key, rotated and then lowered.*

*The RetractaPost-GL is ideal for protecting vehicle forecourts, commercial premises, car parks and domestic driveways.*

*Shown is the 90mm version of the Stainless Steel RetractaPost-GL 745.*

### **Product Range**

<b>Order Code</b>	<b>Description</b>	<b>Lift-up Weight</b>	<b>Weight</b>
138 130 388	60mm (Stainless Grade 304)	3.4kg	16.4kg
138 130 389	76mm (Stainless Grade 304)	4.0kg	17.0kg
138 130 429	90mm (Stainless Grade 304)	5.0kg	28.5kg
138 130 439	101mm (Stainless Grade 304)	5.8kg	41.0kg

### **Accessories & installation parts**

138 811 290 Spare key (please specify key number/product)

### **Product details**

745mm Tall (When raised).  
1070mm Below Ground.  
Mild Steel Galvanised Socket.  
Grade 304 Stainless Steel Body.

### **Installation & use**

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between the raised posts. An excavated hole of approximately 1,200mm deep and 300mm diameter is required for installation. Provision for suitable drainage must be made (chippings or similar) at the bottom of the hole. The uppermost 3-400mm must be concrete. The lid of the post should be no more than 10mm above finished ground level. Keep the sliding post clean and occasionally lubricate the lock with Ambersil 40+ or similar. This product is guaranteed for 12 months (*if installed and used correctly*).