



### The AUTOPA RPP Removable Parking Post FB

The Removable Parking Post is suitable for areas where occasional access is required. The post is typically locked in place over night and removed during the day. Additional ground sockets are available for storing the post in a convenient location when not in use. The lid has been adapted from a standard RPP to allow the use of FB padlocks.

The RPP FB is available in galvanised and galvanised and coated finish. The post is supplied without a padlock thus allowing the user to specify which FB padlock is required.

### Product Range

Order Code	Description	Lift-out Weight	Weight
138 100 631	Galvanised	8.0kg	17.0kg
138 100 633	Galvanised and Black	8.0kg	17.0kg
138 100 632	Galvanised and Yellow	8.0kg	17.0kg
138 100 634	Galvanised and Colour	8.0kg	17.0kg

### Accessories & installation parts

138 150 204	Additional Ground Socket
138 100 920	FB1 Fire Brigade Padlock (Excludes key)
138 100 924	FB14 Fire Brigade Padlock (Excludes key)
138 100 921	FB1 Fire Brigade Padlock Key
138 100 925	FB14 Fire Brigade Padlock Key

### Product details

914mm above ground.  
 Socket Dimensions 267mm x 152mm x 160mm (h x w x l).  
 76mm outside diameter galvanised steel tube body.  
 Plastic cap.

### Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.  
 The ground socket must be concreted into a hole of approximately 300mm cubed.  
 The flap should be flush with the surrounding ground level when closed.  
 Suitable provision for should be allowed for drainage from the bottom of the excavated hole.  
 This product is guaranteed for 12 months (*if installed and used correctly*).