



## The AUTOPA RPP Removable Parking Post

The Removable Parking Post is suitable for areas where occasional access is required. The post is typically locked in place over night and removed during the day. Additional ground sockets are available for storing the post in a convenient location when not in use.

The RPP is available in galvanised and galvanised and coated finish. The post is supplied without a padlock thus allowing the user to specify their own preferred lock (The RSP variant includes a High Security Lock).

The AUTOPA RPP is shown in galvanised finish.

## Product Range

Order Code	Description	Lift-out Weight	Weight
138 100 601	Galvanised	8.0kg	17.0kg
138 100 603	Galvanised and Black	8.0kg	17.0kg
138 100 602	Galvanised and Yellow	8.0kg	17.0kg
138 100 604	Galvanised and Colour	8.0kg	17.0kg

## Accessories & installation parts

- 138 150 206 Additional Ground Socket
- 138 100 906 40mm Brass Padlock with 2 Keys (Random Key)
- 138 100 907 40mm Brass Padlock with 2 Keys (Identical Key)

## Product details

914mm above ground.  
Socket Dimensions 267mm x 152mm x 160mm (h x w x l).  
76mm outside diameter galvanised steel tube body.  
Plastic cap.


## Installation & use

It is recommended that posts are placed no further than 1,200mm apart to ensure no vehicle may pass between.  
The ground socket must be concreted into a hole of approximately 300mm cubed.  
The flap should be flush with the surrounding ground level when closed.  
Suitable provision for should be allowed for drainage from the bottom of the excavated hole.  
This product is guaranteed for 12 months (*if installed and used correctly*).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103