



## The AUTOPA GFC 1500 Ornamental Mild Steel Bollards

Functional yet striking, this ornamental mild steel bollard is designed to resemble its cast iron relative. The body of the bollard is manufactured from mild steel, galvanised for longevity. A slightly domed cap and two rings of cast iron are welded onto the steel body to complete the design.

The GFC 1500 is available in galvanised and galvanised and coated finishes (RAL/BS numbers must be specified at time of order). Supplied ragged as standard, flanged and removable versions are also available. Removable bollards are secured to a ground socket by means of a padlock (available separately).

Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

## Product Range

Order Code	Description	Lift out weight	Weight
138 120 006	Removable (Galvanised)	14.0kg	18.7kg
138 120 007	Removable (Galvanised and Black)	14.0kg	18.7kg
138 120 009	Removable (Galvanised and Colour)	14.0kg	18.7kg

## Accessories & Installation Parts

138 100 906	40mm Brass Padlock with 2 keys (Random Key)
138 100 907	40mm Brass Padlock with 2 keys (Identical Key)
138 150 206	Additional Socket

## Product details

1000mm above ground  
267mm below ground  
114mm diameter tube  
3mm wall thickness

## Installation & use

Removable bollards require an excavated hole of at least 300mm square and 400mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (*if installed and used correctly*).