



GFC 1700 Removable Ornamental Bollard

The GFC 1700 is an attractive and functional ornamental bollard. The body of the bollard is manufactured from mild steel and galvanised for longevity and features a cast domed cap. Two rings of cast iron are welded onto the steel body to complete the design.

The bollard is available in a galvanised and a galvanised and coated finish (RAL/BS numbers must be specified at time of order). Supplied ragged as standard, flanged and removable versions are also available. Removable bollards are secured to a ground socket by means of a padlock (available separately).

Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

Order Code	Description	Lift Out Weight	Weight
138 120 257	Removable (Galvanised)	15.0kg	19.7kg
138 120 259	Removable (Galvanised and Black)	15.0kg	19.7kg
138 120 258	Removable (Galvanised and Colour)	15.0kg	19.7kg

Accessories and installation parts

138 100 906	40mm Brass Padlock with 2 keys (Random Key)
138 100 907	40mm Brass Padlock with 2 keys (Identical Key)
138 150 206	Additional Socket

Product details

1000mm above ground
267mm below ground
114mm diameter tube
3mm wall thickness

Installation & use

Removable bollards require an excavated hole of at least 300mm square and 400mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (if installed and used correctly).