



The AUTOPA GFC 2000s Ornamental Bollard

Functional yet striking, the GFC 2000s bollard is manufactured from mild steel and galvanised for longevity. A spherical cast iron cap is welded on to the bollard complete the design. This bollard is ideal for providing an aesthetic solution to unauthorised parking and access.

The GFC 2000s is available in a galvanised and galvanised and coated finish. RAL numbers must be specified at time of order.

Eyelets, hooks and chains can be added to these bollards to complete the decorative effect. Please ask for more information.

Product Range

Order Code	Description	Weight
138 120 111	Ragged (Galvanised)	8.4kg
138 120 112	Ragged (Galvanised and Black)	8.4kg
138 120 113	Ragged (Galvanised and Colour)	8.4kg
138 120 114	Flanged (Galvanised)	7.1kg
138 120 115	Flanged (Galvanised and Black)	7.1kg
138 120 116	Flanged (Galvanised and Colour)	7.1kg

Accessories and installation parts

138 100 994	M12 Expanding Bolt (3 required per bollard)
-------------	---------------------------------------------

Product details

1000mm above ground
400mm below ground
76mm diameter tube
3mm wall thickness

Installation & use

Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm cube) by means of three M12 bolts.
Ragged bollards require a hole of at least 400mm deep for casting into concrete.
Ragged bollards are supplied with welded fixing spikes to ensure firm ground anchorage.
This product is guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103