



The AUTOPA GFC 5000 Ornamental Mild Steel Bollards

The AUTOPA range of GFC ornamental bollards combine mild steel tube with cast iron caps and rings. The GFC 5000 is an aesthetically pleasing bollard ideal for providing protection against unauthorised parking or access. The GFC range is ideal for use around pedestrian precincts, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

The GFC 5000 is available in galvanised, galvanised and coated finishes. It is also available in ragged for casting into concrete, flanged for bolting down or removable versions.

The AUTOPA GFC 5000 is shown in a galvanised and coated black with ragged fixing and with optional chain.

Product Range

Order Code	Description	Weight
138 120 087	Removable (Galvanised)	19.0kg
138 120 089	Removable (Galvanised and Black)	19.0kg
138 120 088	Removable (Galvanised and Colour)	19.0kg

Accessories and installation parts

138 100 906	40mm Brass Padlock with 2 keys (Random Key)
138 100 907	40mm Brass Padlock with 2 keys (Identical Key)
138 150 206	Additional Socket

Product details

1000mm above ground
267mm (removable)
114mm diameter tube
3mm wall thickness

Installation & use

Removable bollards require an excavated hole of at least 300mm square and 400mm deep for the socket. AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (*if installed and used correctly*).