



## The AUTOPA Swing Height Restrictor

The AUTOPA Swing Height Restrictor has a standard clearance of 2.05m, limiting access to high sided vehicles and is perfect for use on commercial and industrial sites. The boom of the Swing Height Restrictor can be opened to allow full access when needed and can be locked in the open position if necessary using a second catch post.

Manufactured from galvanised mild steel, the body of the height restrictor is coated red as standard (other colours are available upon request; please state BS/RAL numbers at time of order). The Swing Height Restrictor is available ragged or flanged and can be fitted with a knocking bar and/or a maximum height warning sign upon request.

## Options

| Order Code                                  | Description                                      | Weight |
|---|--|--------|
| 138 106 634                                 | 3m Galvanised and Colour (Flanged) c/w catchpost | 76.2kg |
| 138 106 644                                 | 4m Galvanised and Colour (Flanged) c/w catchpost | 79.8kg |
| 138 106 654                                 | 5m Galvanised and Colour (Flanged) c/w catchpost | 84.7kg |
| 138 106 664                                 | 6m Galvanised and Colour (Flanged) c/w catchpost | 89.5kg |
| 138 106 674                                 | 7m Galvanised and Colour (Flanged) c/w catchpost | 96.8kg |
| <b>Accessories &amp; installation parts</b> |  |        |
| 138 500 725                                 | 3m Knocking Bar                                  | 8.8kg  |
| 138 500 730                                 | 4m Knocking Bar                                  | 11.0kg |
| 138 500 735                                 | 5m Knocking Bar                                  | 15.4kg |
| 138 500 740                                 | 6m Knocking Bar                                  | 18.7kg |
| 138 106 558                                 | Height Restrictor Catch Post                     | 24.2kg |
| 138 106 287                                 | Maximum Height Warning Sign                      |        |
| 138 100 991                                 | M16 Expanding Bolt                               |        |

## Product details

Main Body: 90mm x 90mm square tube  
Knocking Bar: 48mm diameter tube  
Standard Clearance: 2.05m  
3mm wall thickness  
600mm below ground (ragged only)

## Installation & use

Flanged Height Restrictors require bolting down to a suitable concrete surface (not less than 600mm<sup>3</sup>) by means of four M16 bolts per leg.  
Ragged Height Restrictors require an excavated hole of at least 600mm<sup>3</sup> for casting into concrete per leg.  
It is recommended that suitable signs are installed to ensure vehicles are aware of the obstruction.  
This product is guaranteed for 12 months (*if installed and used correctly*).



[www.autopa.co.uk](http://www.autopa.co.uk)  
+44 (0)1788 550556

AUTOPA Limited  
Cottage Leap, Rugby, Warwickshire CV21 3XP

