



The VELOPA Sheffield Cycle Stand

The tubular cycle stand, a familiar sight throughout the UK, allows the frame of the bicycle to be secured by the users own security lock. Suitable for securing two bicycles.

The practical and durable nature of the VELOPA Sheffield cycle stand ensures it has been consistently recommended by cycling groups since its introduction in the 1990's.

Shown are the galvanised and stainless flanged versions of the Sheffield Cycle Stand.

Product Range

Order Code	Description	Weight
138 200 111	Ragged (Galvanised)	9.7kg
138 200 101	Flanged (Galvanised)	8.2kg
138 200 112	Ragged (Galvanised and Black)	9.7kg
138 200 102	Flanged (Galvanised and Black)	8.2kg
138 200 105	Ragged (Galvanised and Colour)	9.7kg
138 200 104	Flanged (Galvanised and Colour)	8.2kg
138 200 107	Ragged (Stainless Grade 304)	6.3kg
138 200 106	Flanged (Stainless Grade 304)	5.6kg

Accessories and installation parts

138 100 994 M12 Expanding Bolt (6 required per stand)

Product details

750mm x 800mm (Height x Length)
48mm outside diameter tube.
300mm below ground (Ragged only)


Installation & use

Flanged versions require bolting to established concrete of at least 300mm³ by means of six 12mm bolts per leg. Ragged versions require setting with concrete into a hole of at least 300mm x 300mm x 450mm (length x width x depth) Allow 800-1,000mm between stands and a minimum of 450mm from any obstruction. This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP



FM 31071 EMS 503166 OHS 552103