



The AUTOPA Fixed Height Restrictor

The AUTOPA Fixed Height Restrictor has a standard clearance of 2.05m and limits access to high sided vehicles such as HGV's and Caravans. Height restrictors are ideal for use on sites where limited overhead clearance will cause problems for high sided vehicles such as multi-story or underground car parks.

Manufactured from galvanised mild steel, the body of the height restrictor is coated red as standard (other colours are available upon request; please state BS/RAL numbers at time of order). The Fixed Height Restrictor is available ragged or flanged and can be fitted with a knocking bar and/or a maximum height warning sign upon request.

Options

Order Code	Description	Weight
138 106 530	3m (Flanged)	69.3kg
138 106 540	4m (Flanged)	72.6kg
138 106 550	5m (Flanged)	77.0kg
138 106 560	6m (Flanged)	81.4kg
138 106 570	7m (Flanged)	88.0kg
Accessories & installation parts		
138 500 725	3m Knocking Bar	8.8kg
138 500 730	4m Knocking Bar	11.0kg
138 500 735	5m Knocking Bar	15.4kg
138 500 740	6m Knocking Bar	18.7kg
138 106 287	Maximum Height Warning Sign	
138 100 991	M16 Expanding Bolt (8 required per Height Restrictor)	

Product details

Main Body: 90mm x 90mm square tube
Knocking Bar: 48mm diameter tube
Standard Clearance: 2.05m
3mm wall thickness
600mm below ground (ragged only)

Installation & use

Flanged Height Restrictors require bolting down to a suitable concrete surface (not less than 600mm³) by means of four 16mm bolts per leg.
Ragged Height Restrictors require an excavated hole of at least 600mm³ for casting into concrete per leg.
It is recommended that suitable signs are installed to ensure vehicles are aware of the obstruction.
This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP

