



Plain Round Bollard 1000 (Galvanised) 48mm - 127mm



The AUTOPA Plain Round Bollard (Galvanised) 48mm - 127mm

AUTOPA's range of Plain Round Bollards offers a simple and cost effective means of establishing control over parking and access. Plain Round Bollards are ideal for use around pedestrian precincts, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

The complete range of Plain Round Bollards is available in diameters from 48mm to 406mm and is available in galvanised only and galvanised and coated finishes.

Options

Order Code	Description	Weight
138 121 043	48mm (Ragged)	5.0kg
138 121 048	48mm (Flanged)	4.0kg
138 121 123	60mm (Ragged)	6.2kg
138 121 128	60mm (Flanged)	4.8kg
138 121 203	76mm (Ragged)	7.9kg
138 121 209	76mm (Flanged)	6.3kg
138 121 284	90mm (Ragged)	9.3kg
138 121 282	90mm (Flanged)	7.3kg
138 121 303	101mm (Ragged)	10.4kg
138 121 308	101mm (Flanged)	8.7kg
138 121 403	114mm (Ragged)	11.9kg
138 121 409	114mm (Flanged)	9.7kg
138 121 503	127mm (Ragged)	21.4kg
138 121 508	127mm (Flanged)	20.0kg

Accessories and installation parts

138 100 994 M12 Expanding Bolt (4 required per post)

Product details

1,000mm above ground
400mm below ground (ragged only)
3mm wall thickness

Installation & use

Ragged bollards require an excavated hole of approximately 400mm³ for installation.
Flanged bollards require bolting down to a suitable concrete surface (no less than 400mm³) by means of four M12 bolts.
AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.
This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP

