



Plain Round Bollard 1000 (Stainless) 60mm - 114mm



The AUTOPA Plain Round Bollard (Stainless) 60mm - 114mm

AUTOPA's range of Plain Round Stainless Steel Bollards is a simple and elegant way of controlling vehicle parking and access. Plain Round Stainless Steel Bollards are ideal for use around pedestrian precincts, shops, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

Plain Round Stainless Steel Bollards are available in diameters from 60mm to 204mm and in Grade 304 or Grade 316 Stainless Steel.

Options

Order Code	Description	Weight
138 125 061	60mm (Ragged)	4.4kg
138 125 062	60mm (Flanged)	3.5kg
138 125 076	76mm (Ragged)	5.6kg
138 125 077	76mm (Flanged)	4.4kg
138 125 089	89mm (Ragged)	6.5kg
138 125 091	89mm (Flanged)	5.1kg
138 125 101	101mm (Ragged)	7.3kg
138 125 106	101mm (Flanged)	5.7kg
138 125 114	114mm (Ragged)	8.3kg
138 125 116	114mm (Flanged)	6.5kg

Accessories and installation parts

138 100 994 M12 Expanding Bolt (4 required per post)

Product details

1,000mm above ground
400mm below ground (ragged versions)
2mm wall thickness

Installation & use

Ragged bollards require an excavated hole of approximately 400mm³ for installation.
Flanged bollards require bolting down to a suitable concrete surface (no less than 300mm³) by means of four M12 bolts.
AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them.
This product is guaranteed for 12 months (*if installed and used correctly*).



www.autopa.co.uk
+44 (0)1788 550556

AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP

