

# DECORALE

## DECORATIVE & ACOUSTIC WALLING SOLUTIONS

Description	Test Standard	Acoustic Wallcovering
Product Name		Decorale
Construction	-	Polyester fibres thermally bonded in a non woven matrix, laminated to a high density non woven polyester backing
Fibre Type	-	Fine Velour finish
Total Thickness ( $\pm 10\%$ )	-	9 - 10mm
Total Weight ( $\pm 10\%$ )	-	1600g/m <sup>2</sup>
Pile Weight ( $\pm 10\%$ )	-	810g/m <sup>2</sup>
Dimensions	-	SHEET: 1200mm wide x selected length TILE: 60 x 60cm
Flammability	AS 1530	Ignitability Index (Scale 0-20): 12
		Spread of Flame Index (Scale 0-10): 0
		Heat Evolved Index (Scale 0-10): 4
		Smoke Developed (Scale 0-10): 5
Classification	BS 476 Part 7	Class IV

All weights and thickness quoted  $\pm 10\%$ . Due to batch variation, production material may vary in colour from samples shown in this folder.

### Installation

Affix to wall lengthways using suitable tacky adhesive or tape, butt jointing each panel to the next. Edges can be finished using suitable edging strips. Please contact the Rawson Carpet Solutions Sales Team should you wish to be referred to a competent installer.

### Maintenance

This product is extremely durable and requires little attention to maintain good appearance. Light vacuuming on a regular basis will help to prevent dust building up. Most marks can be cleaned with a mild detergent solution, followed by rinsing and blotting. More stubborn stains can be removed using proprietary household cleaning products. Before carrying out any cleaning, always test any products on a small section in a less visible area to ensure compatibility. Avoid severe abrasion and vacuum to restore pile, never use a stiff brush. Rawson do not recommend using solvent based cleaning products on this product.

Should you require further assistance with the cleaning and maintenance of these wallcoverings, Rawson recommend contacting a professional cleaning company.

### Environmental Information

- All Rawson carpet sheet and tile products are made in the UK.
- Wherever possible, raw materials are sourced in the UK.
- Continuous assessment and improvement of manufacturing process is implemented to minimise use of raw materials/power.
- Whenever possible manufacturing waste is recycled.



Castle Bank Mills, Portobello Road, Wakefield, West Yorkshire, WF1 5PS

Tel: 01924 382860 Fax: 01924 366204

Email: [rcsales@werawson.co.uk](mailto:rcsales@werawson.co.uk)

[www.rawsoncarpetsolutions.co.uk](http://www.rawsoncarpetsolutions.co.uk)

