

# FANFARE

## LUXURY LOOP PILE CARPET TILES

Description	Test Standard	Tiles
Product Name		Fanfare
Construction	ISO 2424	Tufted Loop Pile
Fibre Type	ISO 2076	100% SD Polyamide
Primary Backing	ISO 2424	PES Non Woven
Secondary Backing	ISO 2424	Bitumen
Pile Weight ( $\pm 10\%$ )	ISO 1958	750g/m <sup>2</sup>
Total Weight ( $\pm 10\%$ )	ISO 8543	4540g/m <sup>2</sup>
Pile Height ( $\pm 10\%$ )	ISO 1766	3.4mm
Total Thickness ( $\pm 10\%$ )	ISO 1766	7mm
Pile Density	ISO 1959	0.115g/cm <sup>3</sup>
Stitch Density	ISO 1763	96,457 tufts/m <sup>2</sup>
Dimensions	BS 4939/ISO 3416	50 x 50cm
Tiles per Box	BS ISO 2094	20 (5m <sup>2</sup> )
Dynamic Loading	BS 4052	80% recovery
Wear Resistance	EN 1307	Class 33
Permanent Anti Static	-	Yes
Flame Retardance	ISO 13501-01	Bfl-S1
Hot Metal Nut	BS 4790	Low radius char Grade 1
Castor Chair Rating	BS EN 985A	Pass >2.4
Dimensional Stability	DIN 54318	Pass

All weights and thickness quoted  $\pm 10\%$ . Due to batch variation, production material may vary in colour from samples shown in this folder.

### Installation

All aspects of sub floor preparation and flooring installation must be carried out in accordance with BS 5325:2001 Code of Practice for Installation of Textile Floorcoverings. Sheet carpet should be fully adhered with approved adhesives. The products should be allowed to acclimatise for 24 hours at room temperature (15-20°C) prior to installation. We recommend that the tiles are installed by turning alternate tiles through 90° to obtain a checkerboard pattern and should be adhered with approved adhesives. During both planning and installation, consideration must be given to batch matching and pile direction. For further information contact the Rawson Carpet Solutions Sales Team.

### Maintenance

A regular maintenance programme is always recommended. Use a suction type of vacuum cleaner for daily maintenance. Periodic shampooing and cleaning by a professional cleaning company should be carried out to keep floorcoverings in good condition. Do not use petrol or similar solvents on these products. It is strongly recommended that to prevent excessive flattening, cups and pads are used under heavy furniture and chair mats under castor chairs. With tile products, traffic paths can be avoided by interchanging tiles as necessary.

### Environmental Information

- Rawson products achieve either A or A+ across BREEAM defined building regulations. For specific rating, please refer to [www.breem.co.uk](http://www.breem.co.uk)
- All Rawson carpet sheet and tile products are made in the UK.
- Wherever possible, raw materials are sourced in the UK.
- Continuous assessment and improvement of manufacturing process is implemented to minimise use of raw materials/power.
- Whenever possible manufacturing waste is recycled.



Recommended  
Tile Layout



Recommended  
Tile Layout



**RAWSON**  
CARPET SOLUTIONS

Castle Bank Mills, Portobello Road, Wakefield, West Yorkshire, WF1 5PS

Tel: 01924 382860 Fax: 01924 366204

Email: [rcales@werawson.co.uk](mailto:rcales@werawson.co.uk)

[www.rawsoncarpetsolutions.co.uk](http://www.rawsoncarpetsolutions.co.uk)

