



## HUSH BOND PANEL ADHESIVE

Hush Bond Panel Adhesive is used to ensure a strong bond at the t&g joints of Hush Panel or any other bonding required when fitting Hush sound insulation products and systems.

### PRODUCT DATA

- For bonding all tongue and groove flooring joints and tops of Hush Felt 25
- 1 Litre nossed bottles singularly or in cartons of 9
- 1 litre per 20/ 25m<sup>2</sup>



## HUSH GROMMETS

Hush Grommet Fixing Isolators have been designed for use at door thresholds, access hatches and stair treads or in the absence of t&g joints and should be used sparingly as fixing isolators to eliminate "lipping"

### PRODUCT DATA

- Countersink into the upper surface of the Hush-Panel Floating Flooring. Use sparingly and when only absolutely necessary.
- Available in packs of 50 and 100



## HUSH ACOUSTIC & INTUMESCENT SEALANT

Hush Acoustic sealant is for use in gap filling around room perimeters of surface penetrations or wherever there is a need for acoustic seal to be made when installing Hush products or systems.

### PRODUCT DATA

- General gap filling in acoustic systems
- 900ml nossed tubes sold singularly or in cartons of 9. Jumbo sealant gun required which is also available



## HUSH MESH FIREWIRE

Used in conjunction with Hush Slab 100 Sound Absorber to create a 60 minute fire resistance at ceiling level. Hush Mesh Firewire enables work to be carried out from above in situations where appropriate fire resistance cannot be applied to the ceiling side of the separating floor.

### PRODUCT DATA

- Dressed down the sides of timber joists and across the back of the Ceiling
- 1200mm wide x 50m long --- total 60m<sup>2</sup> per roll



## HUSH 10 JOIST STRIPS

SOLD ONLY WITH HUSH PANELS

Hush 10 Joist Strips are supplied only as part of a system to allow Hush Panel 28, 32 and the Hush Ply 28, 32 to be fitted as a direct to joist structural floor solution.

### PRODUCT DATA

- Stapled directly on to timber joists of glued on to metal joists as part of a Hush-Panel Floating Floor System
- 10mm thick x 50mm wide x 1.37m long



## HUSH ISOLATION TAPE

Hush Heavy Duty Isolation Tape has been designed as an isolating layer to be used under timber/metal stud walls or on top of floor joists.

It is imperative to isolate joist tops, the header/sole plates of stud construction and seal all wall linings to break sound transmission paths. Hush Heavy Duty Isolation Tape can be used for all these applications and is self adhesive one side.

### PRODUCT DATA

- To be used to isolate sole and header plates of timber/metal stud walls or at the perimeter junctions of the Hush Wall System.
- Self-adhesive foam/rubber tape which is easily installed.
- Improves acoustic performance in stud wall construction.

- Isolates chipboard, plywood or original floorboards from the structural timber joists.
- 10m rolls. Comes in 50mm and 100mm widths.
- Nominal 8mm thick.

