

Global leaders in flexible couplings,
drainage & plumbing systems

Lateral Connections

Lateral Pipe Adaptor



A Lateral Pipe Adaptor is a special short length connection to adapt different DN100/150 outside diameter pipes to a PA, DN160 QwikSeal or DN160 TA Saddle.

Lateral Pipe Adaptors enable the connection of DN100 and DN150 pipes into a main sewer.

Product Range

Product Code	Lateral Pipe Size Suitability
PA110	Suitable for all DN100 pipes with an outside diameter between 110-122mm
PA130	Suitable for all DN100/DN125 pipes with an outside diameter between 121-136mm
PA140	Suitable for all DN100/DN125 pipes with an outside diameter between 130-145mm
PA170	Suitable for all DN150 pipes with an outside diameter between 161-175mm
PA180	Suitable for all DN150 pipes with an outside diameter between 170-192mm
PA200	Suitable for all DN200 pipes with an outside diameter between 190-215mm

Product specification for Flexseal Lateral Pipe Adaptors

Product Code	PA110, PA130, PA140, PA170, PA180, PA200
Description	Flexseal Lateral Pipe Adaptor
Size Range	DN100 / DN150 / DN200 Lateral pipe
Material	Main body: EPDM Rubber; Spigot: ABS
Steel	1.4301 (304) Stainless Steel or 1.4401 (316) Stainless Steel (on request)
Pressure Rating	Watertight to 0.5 bar / 8.70 Psi (Application rating will be determined by lateral connection used)
Temperature Range	-50°C to 80°C constant, 100°C intermittent
Tightening Torque	6 Nm
Coupling Standards	EN 295-4; EN 681-1