



### **The PROCTER Height Restrictor (Swing)**

The PROCTER Height Restrictor (Swing) is designed to restrict access to high sided vehicles such as HGV's and Caravans, the swing version has the benefit that it can allow occasional access where delivery vehicles or refuse collections may be required.

The standard clearance is 2.05m (+/- 70mm). The Height Restrictor is constructed of heavy duty 120mm square steel with a 400mm square 10mm thick base plate. The steel is galvanised to ensure longevity and painted red (other colours available, on request). The knocking bar (where fitted) is 48mm diameter tube, painted white with red reflective bands.

The Height Restrictor is available in both a Ragged (for casting in to new concrete) and Flanged feet (for bolting to existing concrete), and is also available in galvanised and galvanised & coated finishes without the knocking bar. An additional catch post is also available where the Swing Arm requires locking in the open position.

### **Product Range**

<b>Order Code</b>	<b>Description</b>
138 106 630	3.0m Height Restrictor Swing - Flanged, including knocking bar (Galvanised & Coated)
138 106 640	4.0m Height Restrictor Swing - Flanged, including knocking bar (Galvanised & Coated)
138 106 650	5.0m Height Restrictor Swing - Flanged, including knocking bar (Galvanised & Coated)
138 106 660	6.0m Height Restrictor Swing - Flanged, including knocking bar (Galvanised & Coated)
138 106 670	7.0m Height Restrictor Swing - Flanged, including knocking bar (Galvanised & Coated)

*(All sizes are measured between the inner edges of the Flanges)*

*Please refer to the Price List for the full range.*

### **Accessories & installation parts**

138 106 287	'MAX. HEIGHT 2.05 METRES' Warning Sign
138 106 558	Catch Post for Swing Height Restrictor (Please specify Ragged or Flanged)
138 100 990	M16 Foundation Bolt (4 required per barrier)

### **Product details**

Standard Clearance; 2.05m (+/- 70mm)

Base Plate; 400mm x 400mm x 10mm.

Main Tube; 120mm x 120mm.

Galvanised steel, painted Red.

48mm knocking bar, coated white with Red Reflective Tape.

### **Installation & use**

Height Restrictor (Fixed) requires bolting down to a suitable concrete surface (not less than 600mm cubed) by means of four 16mm anchor bolts (Flanged).

It is recommended that suitable signs are placed to ensure vehicles are aware of the obstruction.

This product is guaranteed for 12 months (*if installed and used correctly*).

**Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@ProcterContracts.co.uk**