



The PROCTER Illuminated Bollard

The PROCTER illuminated bollard is a commercial and public standard bollard, suitable for all areas accessible to the public, from city squares, public parks to university campuses and hotel grounds. The highly robust construction and design are manufactured to all relevant standards thus ensuring the longevity of the bollards in the most challenging environments.

The 70W SON-E lamp is housed in an aluminium light diffuser which is protected by a polycarbonate sleeve. The illuminated bollard is rated to IP54 and is CE Marked.

The illuminated bollard is available in a ragged only finish and is available in black (as standard) or a range of RAL colours.

Product Range

Order Code	Description	Weight
138 122 500	Illuminated Bollards (Galvanised and painted)	18.0kg

Product details

1,000mm Tall.
 500mm below ground.
 139mm outside diameter steel tube.
 Galvanised steel finish.

Installation & use

Ragged bollards require a hole of at least 500mm deep for casting into concrete.
 Ragged bollards are supplied with welded fixing spikes to ensure firm ground anchorage.
 The illuminated bollard requires connecting to mains 240v AC electricity. This work MUST be completed by a suitably qualified electrician.
 A full technical file detailing all electrical safety test results, approvals, conformances and light dispersal patterns is available on request.
 This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk

Procter Contracts - North
 Isabella Road
 Leeds
 LS25 2DY

Procter Contracts - South West
 11 Pantglas Industrial Estate
 Bedwas
 CF83 8XD

Procter Contracts -South East
 Codham Hall
 Brentwood
 CM13 3JT



The PROCTER Stainless Illuminated Bollard

The PROCTER Stainless Illuminated Bollard is a commercial and public standard illuminated bollard, suitable for all areas accessible to the public, from city squares, public parks to university campuses and hotel grounds. The highly robust construction and design are manufactured to all relevant standards thus ensuring the longevity of the Stainless Illuminated Bollard in the most challenging environments.

The 70W SON-E lamp is housed in an aluminium light diffuser which is protected by a polycarbonate sleeve. The Stainless Illuminated Bollard is rated to IP54 and is CE Marked.

The Stainless Illuminated Bollard is available in a ragged only finish.

Product Range

Order Code	Description	Weight
138 122 550	Stainless Illuminated Bollard	16.0kg

Product details

1,000mm Tall.
 500mm below ground.
 154mm outside diameter steel tube.
 Stainless steel (Grade 304) finish.

Installation & use

Ragged bollards require a hole of at least 500mm deep for casting into concrete.

Ragged bollards are supplied with welded fixing spikes to ensure firm ground anchorage.

The Stainless Illuminated Bollard requires connecting to mains 240v AC electricity. This work MUST be completed by a suitably qualified electrician.

A full technical file detailing all electrical safety test results, approvals, conformances and light dispersal patterns is available on request.

This product is guaranteed for 12 months (*if installed and used correctly*).

Tel Sales : 02920 855756 - Fax : 02920 887005 - Email : Enquiries@procterContracts.co.uk