


Forticrete[®]roofing




Low Pitch Roof Window System

For more light at low pitches


Window frame




Kerb




Side flashings





Top flashing



Bottom flashing



Patented two piece tray system



The patented two piece tray system sits over the roofing underlay but below the battens.

The tray system, roof window and flashings integrate to form a barrier – with any rainwater which has found a way under the tiles dispersed into the guttering system in a controlled manner.


The solution for roof windows as low as 10°...

Before now, the minimum pitch for most roof window installations has been 15°, and even at that pitch problems can occur.

At Forticrete we recognise that often homeowners will want a lower pitch roof to enable them to extend their property as far as they can – particularly with the recently relaxed planning regulations. We also understand the benefit of natural light to a home – so we have invested significant research and development into designing a roof window system which can be installed into a lower pitch roof.

Conventional roof windows and flashing kits work by discharging water up and over the face of the tiles. At lower pitches water does not run off so quickly and can therefore pool and lead to water ingress. The Forticrete Low Pitch Roof Window System solves this using a patented two-piece tray drainage flow system, which collects any water which runs under the tiles and disperses it across the trays, over the fascia and into the gutter in a controlled manner.

Fakro FTP-V
U3 Centre
Pivot Window



Scan the QR code with your smartdevice for instant access to the latest information.



Bring more light into your home naturally using the Forticrete Low Pitch Roof Window System

Your Low Pitch Roof Window System includes:


- Fakro FTP-V U3 Centre Pivot Window and flashing kit
- Innovative, patented 2 piece tray system
- Packs to fully ventilate eaves and abutment
- A 10 Year system guarantee

Centurion[®]10

It is recommended that the Forticrete Low Pitch Roof Window System is installed with Centurion[®] low pitch interlocking roof tiles. Capable of being laid to a rafter pitch as low as 10° degrees, the Centurion[®] tile boasts wind barriers behind its leading edges which provide a highly effective barrier against the elements. This makes the Centurion[®] the ideal tile solution for low pitched roofs, particularly for single storey extensions with restricted height constraints or new build projects with a low pitch design. It is available in four colours and a full range of dry fix fittings to suit all applications.



Centurion[®] Red



Autumn



Red



Brown



Slate Grey

Forticrete®stone



Anstone® and Shearstone™ walling stone



Recreate the appeal of natural stone walling with confidence.

With the appearance and weathering qualities that are almost indistinguishable from natural stone, the popular finishes - split, pitched and cottage are available in colours specifically designed for regions throughout the UK.

For sales enquiries please contact our Anstone office on **01909 775000**
Email us at walling@forticrete.com
or visit www.forticrete.co.uk



Walling stone

Forticrete®masonry



Linear

Elegant, colourful and wonderfully long concrete bricks.

A multitude of colours together with textures ranging from simple textured to highly polished - the Linear range has been created to give architects the flexibility to create distinctive exteriors.

For sales enquiries please contact our Thornley office on **01429 838 001**
Email us at masonry@forticrete.com
or visit www.forticrete.co.uk



Linear

Forticrete®stone



Cast stone dressings



Time honoured craftsmanship and advanced technology working together in perfect harmony.

Cast Stone Dressings are available ex-stock as Stone-in-Stock, or cast from standard moulds in six classic colours. Purpose made dressings can also be made to precise specifications.

For sales enquiries please contact our Anstone office on **01909 775000**
Email us at caststone@forticrete.com
or visit www.forticrete.co.uk



Cast Stone

Working procedures, safety & general precautions

Tiles should be fixed in accordance with the current version of BS:5534 at the time of installation. Forticrete recommend that fixers of all slates and tiles regard the products as fragile as stated in BS8000:Pt6:1990 Section 5. During installation of the products, the correct setting out and working procedures should be employed to avoid walking directly on to products which have been fixed or are on any completed area of a roof. Should it be necessary to gain access via the roof where battens of adequate strength cannot be used as footholds, this should not be attempted without the use of adequate protection to the tiles or slates including the required number of crawling boards, ladders and cat ladders.

Please note that where there is a change of pitch, packing may be required between crawling boards, cat ladders and the surface of the tiles or slates to avoid damage to the product. Fixers should note that Forticrete do not recommend the practice of cutting tiles or slates in-situ. Other information can be obtained from the Health and Safety in Roof Work publication HSG33 and in the 'Working on Roofs' publication INDG284. Reference should also be made to the Forticrete Technical Literature and Fixing Instructions.

Order your Low Pitch Roof Window System from:

Roofing Systems & Technical enquiries:

Forticrete Limited,
Boss Avenue, off Grovebury Road,
Leighton Buzzard,
Beds LU7 4SD

Tel: 01525 244900
Fax: 01525 850432
E-mail: roofing@forticrete.com



www.forticrete.co.uk

Forticrete, Centurion, Anstone, Ecotile, Ecowall and the E device are registered trademarks of Forticrete Ltd.

Shearstone is a trademark of Forticrete Ltd.
CRH is a registered trademark of CRH plc.

All relevant Forticrete products are CE marked. Declarations of Performance are available at www.forticrete-ce.com

Forticrete is a CRH Company

This document does not form part of any contract and Forticrete cannot accept liability for any errors or omissions.

In order to maintain its position as a market leader, Forticrete operates a policy of continuous product development and therefore reserves the right to alter specifications without notice.

Although the instructions contained in this publication and any other information published by Forticrete are believed to be accurate at the date of publication, they are strictly for guidance only and Forticrete accepts no liability in relation to their use or for any losses, howsoever caused. You are responsible for taking all reasonable steps to ensure your use of the goods/products conforms to all applicable health and safety requirements from time to time. If in doubt, please consult appropriately qualified persons. All products sold by Forticrete are sold subject to Forticrete's Terms and Conditions of Sale, a copy of which is available on request.

Approved stockist

Forticrete®roofing

© Forticrete Ltd. 2014. All rights reserved.

