

SETSEAL DRIVESEAL

Fast drying acrylic polymer driveway sealer



TECHNICAL DATA SHEET PUBLISHED AUGUST 2016

PRODUCT FEATURES

Setseal Driveseal is a fast drying acrylic polymer based sealer, designed to protect and enhance the appearance of tarmac driveways.

Setseal Driveseal can be used to on new driveways or to refurbish existing driveways, giving an attractive satin finish that provides protection against staining and weather damage.

MATERIALS SUPPLIED

20 Litres.

COVERAGE

6 m² per litre per coat depending on the porosity of the existing substrate and the surface profile.

STORAGE

Store in closed containers above 5°C and under dry, well ventilated warehouse conditions, out of direct sunlight and away from naked flames or other sources of ignition. Protect from frost.

SHELF LIFE

At least 3 years if stored in original containers in appropriate conditions.

SURFACE PREPARATION

Prior to application the surface must be clean, dry, stable and free from loose debris. A stiff broom should be used and a propriety fungicidal wash to remove moss and algae. Oil and grease deposits should be removed with a good quality degreaser, rinsed with clean water and allowed to dry. Any repairs to the tarmac should be made with a propriety cold cure tarmac and allowed to cure prior to application of SETSEAL DRIVESEAL.

New tarmac should be allowed to dry for 90 days prior to application.

APPLICATION

SETSEAL DRIVESEAL should be applied to a sound surface (see surface preparation above).

Mix sealer thoroughly in the tin before pouring into a roller tray. Using a long pile roller, fully load the roller and apply the sealer, painting from the furthest point. The sealer should be stirred periodically in the tray.

CURING TIME

SETSEAL DRIVESEAL may be overcoated after 4 hours, however on cooler, damp days this may be extended. Vehicles may be parked after the 2nd coat has cured for 4 hours. SETSEAL DRIVESEAL should be allowed to cure for 24 hours prior to heavy vehicular use and will continue to cure to optimum hardness over several days.

CLEANING

Once mixing and application are complete, tools can be cleaned with water and detergent.

WORKING CONDITIONS

SETSEAL DRIVESEAL should only be applied in dry conditions and not be applied if it is forecast to rain within 12 to 24 hours. Application should be carried out in temperatures between 10°C and 30°C. Freshly applied product should be protected from frost.

HEALTH & SAFETY

Consult the appropriate Material Safety Data Sheets prior to using SETSEAL DRIVESEAL.

GENERAL GUIDANCE

This Data Sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

Please consult our Sales Department to confirm that this Data Sheet is the current issue.

Don Construction Products Ltd Hawthorn House, Helions Bumpstead Road,
Haverhill, Suffolk CB9 7AA, UK T: +44 (0) 1440 766360

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

 expertise

 quality

 full range