

DECORATORS SKIMCOAT FILLER

A SKIMMING FILLER

**READY
TO USE
JOINTFILLER**

- ▶ **FILL, JOINT, TAPE IN ONE**
- ▶ **ADHERES ON PAINT WORK**
- ▶ **NO PVA REQUIRED***
- ▶ **UP TO 5 MM PER COAT**
- ▶ **PAINT WITHIN 24 H**



PURPOSE

Skimming filler in paste form, for interior use, manual application.

SUBSTRATES

DECORATORS SKIMCOAT FILLER applies on either new or renovated substrates, either unpainted or painted:

- Gypsum plaster, plasterboards/dry wall lining,
- Old painted surfaces,
- Any filler type of **TOUPRET** range,
- Cement, concrete, cellular concrete, breeze block, bricks, stones,
- Fibreglass cloth, slightly or highly structured surfaces finishes,

OVERCOATING

DECORATORS SKIMCOAT FILLER can be over coated with any type of paint, wall coverings or **TOUPRET** fillers.

Physical and technical FEATURES

DECORATORS SKIMCOAT FILLER: Interior filler in paste form, made of selected mineral extracts and resin.

- Characterization (NFT 36-005): Family III - Class 2
- Codification (EN 16-566): $G_3S_2V_0W_0A_0C_0R_0$
- Application thickness: up to 5 mm
- Consumption: 1.7 kg/m²/mm
- Second coat: once filler is dry
- Overcoat: 12 to 24 H average time (after complete drying)
- Colour: white
- Shore hardness: 75
- Adhesion filler/substrate (EN 16-566): > 0,5 MPa
- Up to 5mm per coat, paint within 24 hours.

USE AND STORAGE CONDITIONS

- Application tool: with trowel or blade
- Tools cleaning: with water.
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from sun and frost.

PACKAGING

- Bucket of 10 kg.

* On hard and cohesive substrates.

RECOMMENDATIONS and care for use

- Do not apply on polystyrene, nor on adhesive coverings nor on exterior substrates.
- Do not apply under a temperature < 8 °C and over > 35 °C nor under an hygrometry rate over 70%.
- Do not apply on warm/overheated surfaces
- Do not apply on damp surfaces

SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- EN 16-566 : Coating fillers for interior works and/or exterior.
- NFT 36-005 : Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.
- French DTU 59.4 (NFP 74-204): Setting up of wall papers and wall coatings.

HEALTH AND SAFETY

- No danger tag.
- Safety data sheets available on www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of **DECORATORS SKIMCOAT FILLER** are provided in good faith and result from the knowledge of the products and experience of **TOUPRET** company. The product is required to be applied as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.