

**[READY
TO USE]**

FINE SURFACE FILLER

EXTRA FINE SURFACER

- ▶ **ADHERES ON PAINTED SURFACES**
- ▶ **ENHANCES PAINT FINISH**
- ▶ **NO NEED TO SPOT PRIME**
- ▶ **NO NEED TO SAND**
- ▶ **EXCEPTIONAL SMOOTH FINISH**



PURPOSE

Finish filler in paste form, for interior use, manual application.

SUBSTRATE

FINE SURFACE FILLER applies on either new or renovated substrates, either unpainted or painted:

- Gypsum plaster, plaster tiles, plasterboards,
- Old painted surfaces,
- Any fillers
- Cement, concrete

OVERCOATING

FINE SURFACE FILLER can be overcoated by any type of paints and wall coverings.

Physical and technical FEATURES

FINE SURFACE FILLER: filler in paste form for interior use, made of mineral extracts and selected resin.

- Characterization (NFT 36-005): Family III class 2
- Codification (EN 16-566): $G_3S_1V_0W_0A_0C_0R_0$
- Application thickness: 1 mm (up to 2 mm locally)
- Consumption: 450 à 700 g/m²
- Second coat: once the filler is dry
- Overcoating: 8 Hrs average time (after complete drying)
- Colour: white
- White Index : 70
- Shore Hardness: 80
- Adhesion filler/substrate (EN 16-566): > 0,5 MPa

USE AND STORAGE CONDITIONS

- Application tools: coating or smoothing blade.
- Tools cleaning: the product residues are to be rubbed off when dry. Water cleaning is unnecessary.
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from sun and frost.

PACKAGING

- Tube of 330 g
- Tubs of 1,5 and 4 kg

RECOMMENDATIONS

and care for use

- Do not apply on polystyrene, nor on adhesive coverings, nor on exterior substrates.
- Do not apply under a temperature < 8 °C and > 35 °C nor under an hygrometry rate above 70 %.
- Do not apply on warm/overheated substrates.
- Do not apply on wet/damp substrates.

SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS

to be referred to

- EN 16-566: Coating fillers for interior works and/or exterior .
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.
- French DTU 59.4 (NFP 74-204): Setting up of wall papers and wall coverings.

HEALTH AND SAFETY

- No danger tag.
- Safety data sheets available on www.toupret.co.uk

The data sheet information, especially the guidelines relevant to the application and final use of **FINE SURFACE FILLER** are provided in good faith and result from the knowledge of the products and experience of **TOUPRET** company. The product is required to be applied as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.