



# TOUPRELEX®

## EXTERIOR FAST DRYING LIGHTWEIGHT FILLER



- ▶ **LIGHT GREY COLOUR**
- ▶ **ONE COAT FILL**
- ▶ **VERY HARD: RICH IN RESIN**
- ▶ **NO STABILISING SOLUTION OR PVA REQUIRED\***
- ▶ **WILL NOT FLASH OR GRIN**

### PURPOSE

Ready mixed lightweight filler, for exterior use, manual application.

### SUBSTRATES

TOUPRELEX® applies on either painted or unpainted substrates:

- Gypsum plaster
- Cement, concrete, breeze blocks, bricks, stones
- Old painted surfaces
- Cellular concrete

### OVERCOATING

TOUPRELEX® can be overcoated by all types of paints: mineral paints, waterproofing coatings and TOUPRET exterior fillers. Do not cover straight over with polyurethane or solvent-based epoxy paints.

### Physical and technical FEATURES

TOUPRELEX® is a filler in paste form, for exterior use, made of lightweight calcium carbonate loads and resins.

- Characterization (NFT 36-005): Family IV-4b
- Codification (EN 16-566): G<sub>3</sub>S<sub>2</sub>V<sub>0</sub>W<sub>0</sub>A<sub>0</sub>C<sub>0</sub>R<sub>0</sub>
- Application thickness: no limitation
- Second coat: once the filler is dry
- Overcoat: 1 H average time (once completely dry)
- Colour: light grey
- Adhesion filler/substrate (EN 16-566): > 0.8 Mpa

### USE AND STORAGE CONDITIONS

- Application tools: coating knife, trowel or blade.
- Tools cleaning: with water.
- Preservation: product guaranteed 6 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from humidity.

### PACKAGING

- Tub of 1 and 4 L.

\*On hard, cohesive, clean, sound and dry substrates.

### RECOMMENDATIONS and care for use

- Do not apply on polystyrene, nor on adhesive coverings.
- Do not apply under a temperature < 5 °C and > 35 °C nor under an hygrometry rate over 80%.
- Do not apply on warm/overheated surfaces nor under sun exposure.
- Do not cover straight over with polyurethane or solvent-based epoxy paints.

### SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

### NORMATIVE DOCUMENTS to be referred to

- EN 16-566: Coating fillers for interior works and/or exterior.
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.
- French DTU 42.1 (NFP 84-404): façades renovation with polymer-based waterproofing coatings.

### HEALTH AND SAFETY

- No danger tag.
- Safety data sheets available on [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of TOUPRELEX® are provided in good faith and result from the knowledge of the products and experience of TOUPRET company.

The product is required to be used as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.