

WOOD REPAIR

WOOD REPAIR FILLER

INTERIOR/EXTERIOR



[FAST DRYING]

- ▶ **STAIN OR PAINT IN 3 HRS**
- ▶ **EXCELLENT ADHERENCE**
- ▶ **EASY TO SHAPE AND SAND**
- ▶ **CAN BE DRILLED AND SCREWED**
- ▶ **VERY EASY TO SAND**
- ▶ **LOW ODOUR**



PURPOSE

Filler in powder form, to reconstitute missing wooden parts and repair broken angles. For interior and exterior use. Manual application.

OVERCOATING

WOOD REPAIR can be overcoated by any type of conventional paints, varnishes and stains.

SUBSTRATE

WOOD REPAIR applies on any types of woods, including exotic species, chipboard and plywood.

Physical and technical FEATURES

WOOD REPAIR is a filler in powder form, for interior or exterior use, made of mineral extracts and selected binders.

- Characterization (NFT 36-005): Family IV - Class 4c
- Codification (NFT 30-608): $G_3E_2S_0V_0W_0A_0C_0$
- Mixing rate: 30% water (hence 0.3 litre water for 1 kg powder)
- Application thickness: no limitation
- Working time: 30 minutes
- Second coat: once the filler is dry
- Overcoat: 3 HRS average time (after complete drying)
- Colour: wood beige
- Adhesion filler/substrate (NFT 30-608): > 0,8 MPa

USE AND STORAGE CONDITIONS

- Application tools: coating knife, trowel or blade.
- Tools cleaning: the product residues are to be rubbed off when dry. Water cleaning is unnecessary.
- Preservation: product guaranteed 6 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from humidity.

PACKAGING

- Box of 1 kg

RECOMMENDATIONS and care for use

- Do not apply on polystyrene, nor on damp substrates.
- Do not apply under a temperature < 5 °C and > 35 °C nor under an hygrometry rate over 80%.
- On exterior substrates, Wood Repair is required to be coated over
- On rough (unprepared) wood, it is recommended to apply **TOUPRET WOOD HARDENER** beforehand.

SUBSTRATES PREPARATION

- Substrates to be prepared as per the current trade practices.
- Substrates must be hard, cohesive, clean, sound and dry.

NORMATIVE DOCUMENTS to be referred to

- NFT 30-608: Coating fillers for interior works and/or exterior.
- NFT 36-005: Characterization of paint products.
- French DTU 59.1 (NFP 74-201): Building paint works.

HEALTH AND SAFETY

- No danger tag.
- Safety data sheets available on <http://www.toupretpro.co.uk> or on quickfds.com or toupret.com.

The data sheet information, especially the guidelines relevant to the application and final use of Le **WOOD REPAIR** are provided in good faith and result from the knowledge of the products and experience of **TOUPRET** company.

The product is required to be used as per the trade practices rules book and in reference to our recommendations.

The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates.

The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions.