

# PLASTER OF PARIS

[ TRADITIONAL FILLER ]



- ▶ **QUICK SETTING TIME**
- ▶ **VERY FINE**
- ▶ **EASY TO SAND**
- ▶ **EASY TO PREPARE**
- ▶ **EASY TO SHAPE AND MOULD**

## PURPOSE

Plaster of Paris: interior filler gypsum plaster based, in powder, manual application.

## SUBSTRATES

**PLASTER OF PARIS** applies on unpainted, new or renovated, substrates :

- Gypsum plaster, plaster tiles, plaster boards,
- Cement, concrete, cellular concrete breeze blocks, bricks, stones

## OVERCOATING

**PLASTER OF PARIS** can be coated by any type of paint or wallpaper. Any type of TOUPRET filler.

## Physical and technical FEATURES

- Mixing rate: 75% water (hence 0,75 l water for 1 kg powder)
- Application thickness : not limited
- Consumption: 1 kg powder fills 1.2 l
- Colour : white.
- Working time : 10 to 15 minutes
- Second coat: when the filler is dry
- Painted / overcoated: in 12 to 72 hrs. average time (after complete drying)
- Colour: white

## USE AND STORAGE CONDITIONS

- Application tools : coating knife, blade or trowel.
- Tools cleaning : The product residues can be rubbed off when dry.
- Water cleaning is unnecessary.
- Preservation: product guaranteed 12 months, from the original purchase invoice date as evidence, in its original sealed packaging and stored away from humidity.

## PACKAGING

- Bag of 4 kg

## RECOMMENDATIONS and care for use

- Do not apply Plaster of Paris on polystyrene nor on wall paper nor on exterior located substrates.
- Do not apply: under a temperature below 5°C nor above 35°C nor under an hygrometry rate above 70%.
- Do not apply on overheated substrates.
- Do not apply on wet substrates.
- Do not mix the paste any longer once it has begun to set.
- Do not cover with cement or concrete.

## SUBSTRATES PREPARATION

- The substrates to be prepared as per the current professional practices. (French DTU)
- The substrates must be hard, cohesive, clean sound and dry.

## NORMATIVE DOCUMENTS to be referred to

- EN-13279-1 : gypsum based binders and fillers for building works
- France DTU 25.1: gypsum based filler for interior use

## HEALTH AND SAFETY

- No danger tag.
- Very low VOC emissions : <0,25%
- Safety data sheets available on [www.toupret.co.uk](http://www.toupret.co.uk)

The data sheet information, especially the guidelines relevant to the application and final use of **PLASTER OF PARIS** are provided in good faith and result from the knowledge of the products and experience of TOUPRET Company. The product is required to be used as per the trade practices rules book and in reference to our recommendations. The information provided is relevant to applications processed under a temperature of 20°C, a hygrometry rate of 50 % and on normal-absorbent substrates. The times mentioned are only indicative and depend on the substrate, the coat thickness, and the ambient conditions



Information on the level of emission of volatile substances in indoor air, presenting a risk of inhalation toxicity, on a class scale from A + (very low emissions) to C (high emissions).