

Telescopic Gates

SG-TG-002

A telescopic gate has the advantage that it takes up less space compared to a tracked or cantilevered sliding gate when in the open position. This therefore makes it ideal for a site where space is restricted either side of an entrance, but where the entrance itself is relatively wide - a single telescopic gate can be used for an opening of up to 14m, and a pair of gates for an opening of twice that size.



The final specification will take account of factors such as the level of security required and most suitable access control system, as well as aesthetics (e.g. complementing the adjacent fence design and adding company logos) - all of which we are able to do.

Applications

Warehousing

Secure sites

Utilities

Airports

Retail

Industrial Units



Product Data

Finish	Hot dip Galvanised to BS EN ISO 1461:2009 and polyester coated to a range of RAL colours
Gate Height (Gate heights available to suit your application)	1.8m ~ 2.4m
Gate Opening Width (wide range of widths available to suit your application)	14m single ~ 28m double
Material available	<ul style="list-style-type: none"> • steel balustrade • welded mesh • decorative infill panels • timber cladding • bespoke designs.
<p>* Matching Pedestrian Gate Available</p> <p>* Automation and Access Control Available (Including CE marked safety equipment, meet Health & Safety requirements)</p>	<p>** Cantilever and Tracked Sliding Gates available, please ask for relevant Datasheet for your interest.</p>



Southern Area Office
Procter Automatic Gates
Pantglas Industrial Estate
Bedwas, Caerphilly CF83 8XD
Tel : 02920 882 111
Fax: 02920 888 544

Northern Area Office
Procter Automatic Gates
Isabella Road
Garforth, Leeds LS25 2DY
Tel : 0113 287 6282
Fax: 0113 287 6284

South East Office
Procter Automatic Gates
Codham Hall, Great Warley Brentwood,
Essex CM13 3JT
Tel : 02920 855 756
Fax: 02920 888 544