

Standard Grade

Standard Grade is extremely versatile and can be used below DPC, as infill for beam and block flooring systems, as well as above the ground in the walling applications listed.



Standard Grade
(no colour line)



Celcon Blocks, Standard Grade are BBA certified and available in thicknesses from 75mm up to 355mm. Due to its all round performance, it is possible for 100mm Standard Grade Block to be used throughout a build – in floors and all walls eliminating any site confusion.

Applications

- Internal and external leaf of cavity walls
- Solid walls
- Separating walls
- Partitions
- Multi-storey buildings
- Foundations
- Beam and Block floors
- Flanking walls



Standard Grade



Standard Grade


Celcon Foundation Block
325 x 215mm




Scratch Marked Celcon Block
440 x 215mm
and Foundation Blocks (all sizes)



Plain Face Celcon Block
440 x 215mm
and Foundation Blocks (all sizes)



Celcon Block Coursing Unit
215 x 65mm



Plain Face Celcon Plus Block
630 x 215mm



Plain Face Jumbo Bloks
630 x 250mm



Celcon Blocks Standard Grade

	Standard Grade
Compressive Strength	3.6N/mm ²
Thermal Conductivity	0.15 W/mK*
Density	600 kg/m ³

For further information and to check our most up-to-date product range, or to find your nearest stocking merchant, please visit our website www.hhcelcon.co.uk or contact the following departments:

Sales

For sales enquiries or to find your local stockist please contact
Tel: 01732 886444
Fax: 01732 887013

Technical

For technical enquiries please contact
Tel: 01732 880580
Fax: 01732 887013