

DEVireg 130



The DEVireg 130 is a simple electronic thermostat to be installed directly on the wall, using a floor sensor (wire) to measure and control the desired floor temperature.

The thermostat has a dial for adjusting the temperature setting with a scale from 1 to 5. Furthermore, the thermostat has an LED indicating the current mode (heating, standby or fault).



Benefits:

- Double pole safety breaker
- LED indication
- Floor sensors
- 2 year warranty

Type	Value
Operation voltage:	220 V- 240V~
Standby power consumption:	Max. 5 W
Relay:	
Resistive load	Max 16A / 3680W @ 230V
Inductive load	Cos Φ = 0.3 max. 1A
Sensing unit:	NTC 15 kOhm at 25° C
Hysteresis:	± 0.2° C
Ambient temperature:	-10° C. to +30° C
Frost protection:	5° C - ❄
Temperature range:	5° C - 45° C
Cable specification max:	1 x 4 mm ² or 2 x 2.5 mm ²
Ball pressure test temperature:	75° C
Pollution degree:	2 (domestic use)
Controller type:	1 C
Storage temperature:	-20° C to +65° C
Protection class:	Class II
IP class:	30
Dimensions (H x W x D):	82 mm x 82 mm x 36 mm
Weight:	90 g

Stock Code	Product Name	Type	Dimensions (H x W x D)
140F1010	DEVireg 130	With floor sensor	82mm x 82mm x 36mm

