



Cuprinol One Coat Sprayable Fence Treatment

About this product

Cuprinol One Coat Sprayable Fence Treatment has been specially formulated to work with the Cuprinol Sprayers to colour and protect rough sawn timber in a fraction of the time. Its special pigments ensure rich colour and even coverage in just one coat. Cuprinol One Coat Sprayable Fence Treatment is quick drying, low odour and safe to use around plants and pets.

Key Benefits

- ✓ Colour and weather protection
- ✓ Even coverage in 1 coat
- ✓ For use with Cuprinol sprayers or a brush
- ✓ Water based

Special Features

- ✓ Brush or spray

Technical Information

Coverage

5L covers up to 15m² with 1 coat or 5 fence panel sides

Product Information

Typical Use

Bare or untreated wood should be pre-treated with an appropriate wood preserver to prevent rot and decay. Surfaces should be dry and free from dirt and algae etc. Remove any algae, lichen, fungi or moss using an appropriate fungicidal wash or cleaner designed for the job.

Composition

Water-based

Key Benefits

Colour and weather protection, Even coverage in 1 coat, For use with Cuprinol sprayers or a brush, Water based

Pack size

5L

Application Method

Shake the pack thoroughly before use. Final colour will depend upon wood type, previous treatment and the number of coats applied. Apply using the appropriate Cuprinol sprayer for the product. As with any sprayer it may take a couple of minutes to perfect your technique. Ensure you stand at the correct distance with the nozzle 15-30cm (6"-12") from the wood surface. Begin slowly and increase the pace as you get used to spraying. Take care not to spray too quickly as this may result in an uneven finish.

Similarly, spraying too slowly will result in excess product being applied causing runs. Should this happen, simply brush into the wood. Avoid spraying surrounding plants, brickwork, glass, PVCu, etc. Overspray can be minimised by avoiding spraying in windy conditions and by using cardboard or plastic as a shield.

Any overspray should be cleaned up immediately (whilst still wet) with water and household detergent.

Excessive spillage on plants should be rinsed off immediately before drying. If applying by brush, apply evenly, avoiding splashing surrounding plants, brickwork, glass, PVCu, etc. Do not apply in temperatures below 5C, in damp conditions or if rain is likely before the product has dried. Cover any surfaces nearby to protect from overspray. Allow 2-6 hours between coats under normal weather conditions. Where a strong colour change is involved, more coats may be required. Product performance will be reduced if applied to grey and weathered smooth wood. If using more than one pack it is advisable to mix them together in a larger container or finish in a corner before starting a new pack.