



## Cuprinol UV Guard Decking Oil

### About this product

Cuprinol UV Guard Decking Oil can be used to penetrate into wood to replace natural oils and resins lost through weathering. Its tinted formula revitalises the natural colour of weathered wood. Ideal for softwood.

### Key Benefits

- ✓ Nourishes the wood and protects against the weather
- ✓ Lightly tinted finish
- ✓ Application by brush or any Cuprinol sprayer
- ✓ Water based

### Special Features

- ✓ Easy application

### Technical Information

#### Coverage

A 2.5L can covers up to 20m<sup>2</sup> with 2 coats brush applied. A 5L can covers up to 40m<sup>2</sup> with 2 coats brush applied or 1 coat spray applied. Coverage can vary depending on application method and the condition and nature of the surface

### Product Information

#### Typical Use

Read the Health, Safety and Environmental Information on pack. Ensure timber used in ground contact has been pretreated or sold specifically for use as decking. Remove excessive dirt and soiling, large areas of algae, lichen, fungi or moss with a scraper or stiff brush suitable for use on grooved decking. Treat the surface with a fungicidal wash or cleaner designed for the job. For grey and weathered decking use

Cuprinol Decking Restorer to bring back the natural colour. Only suitable for use on bare or previously oiled decking.

**Composition**

Water-based

**Key Benefits**

Nourishes the wood and protects against the weather, Lightly tinted finish, Application by brush or any Cuprinol sprayer, Water based

**Pack size**

2.5L, 5L

## Application Method

Shake can well before and frequently during use. Brush on evenly along the grain. Apply a second coat if required once the first coat has penetrated into the wood. Do not allow puddles to form.