



Hammerite Red Oxide Primer

About this product

Hammerite Red Oxide Primer is specially formulated for use on both bare and rusty iron and steel. For aluminium, galvanised and all other non-ferrous metals, use Hammerite Special Metals Primer

Key Benefits

- ✓ A high performance anticorrosive formulation
- ✓ Quick drying.
- ✓ Can be used inside or outside
- ✓ Use on gates, railings and metal drainpipes
- ✓ Solvent based

Special Features

- ✓ A high performance anticorrosive formulation
- ✓ Quick drying

Technical Information

Touch dry	2 hours
Recoatable	6 hours
Coverage	12m ² per litre

Product Information

Typical Use

All surfaces must be clean and dry. Remove loose rust, scale and paint with a wire brush then rub down

with coarse abrasive paper to provide a firm surface. Abrade bare steel with coarse abrasive paper. Degrease all surfaces with Hammerite Brush Cleaner & Thinners and allow to dry

Composition

Solvent-based

Key Benefits

A high performance anticorrosive formulation, Quick drying,, Can be used inside or outside, Use on gates,railings and metal drainpipes, Solvent based

Pack size

250ML, 500ML

System Information

Stir paint thoroughly. For best results when applying by roller, use a short pile mohair roller. Apply 2 coats of Hammerite Red Oxide Primer, allowing a minimum of 6 hours between coats. A topcoat may be applied after a minimum of 6 hours. For best results, allow 24 hours. Hammerite Red Oxide Primer can be overpainted with most paints.

Application Method

Stir paint thoroughly. For best results when applying by roller, use a short pile mohair roller. Apply 2 coats of Hammerite Red Oxide Primer, allowing a minimum of 6 hours between coats. A topcoat may be applied after a minimum of 6 hours. For best results, allow 24 hours. Hammerite Red Oxide Primer can be overpainted with most paints.