



Sikkens Cetol BL Opaque

About this product

Cetol BL Opaque has been specially formulated using woodstain technology to give a flexible, paint-like finish, which is an environmentally preferable alternative to traditional paint.

Key Benefits

- ✓ Covers blemishes in wood without hiding the natural grain texture
- ✓ Long lasting and more sustainable alternative to traditional opaques.
- ✓ Outstanding covering power and adhesion.
- ✓ Flexible and vapour permeable formulation for added durability.

Special Features

- ✓ Excellent Adhesion

Technical Information

Touch dry	1 hour
Recoatable	6 hours
Coverage	6-12 m ² /L

Product Information

Composition

Water-based

Key Benefits

Covers blemishes in wood without hiding the natural grain texture, Long lasting and more sustainable alternative to traditional opaques., Outstanding covering power and adhesion., Flexible and vapour

permeable formulation for added durability.

Colour Range

CUPRINOL Digital Default Colors (Web Only), Sikkens Cetol Colour Collection (Painters)

Pack size

2.5L, 4.65L, 4.75L, 5L

Application Method

Conditions: Do not apply if there is a risk of rain, or when air/substrate temperatures are below 8°C or above 25°C during

application or drying periods. Protect from frost and rain until dry. Failure to meet these requirements may adversely

affect the drying, visual quality and durability of the finish.

After applying one coat allow a minimum of 6 hours drying time before overcoating. On new work, where practical the first coat should be applied all round prior to fixing. Pay special attention to exposed end grain, tops and bottoms of doors, and undersides of cills. Where appropriate (e.g. windows and doors), carefully denib the coat using a fine grade nylon abrasive pad or a fine grade (P240 or finer) wet or dry silicon carbide abrasive paper. Remove all dust.

Subsequent coatings should be applied as soon as possible after the previous coat has dried, but no sooner than 6 hours,

in order to provide full protection. In any event this period should not extend beyond three months, otherwise additional

preparation and coating may be necessary. If applied to exterior wood and the contract is of long duration, it is suggested that a further coat be applied prior to hand over to make good any weathering during the construction period. Ensure product is thoroughly stirred before and during application, otherwise sheen and colour variations may be experienced. Cetol BL Opaque is supplied ready for use. Do not thin. For best results use a good quality synthetic-fibre brush specifically designed for the application of water-borne products. Apply product in a full flowing coat, laying off in the direction of the grain. Use the minimum number of brushstrokes required for an acceptable finish. Avoid overbrushing, which creates brush marks and produces a poor quality finish. Coating system durability can be improved by use of end grain sealers. Cetol BL Opaque is a two-coat system on most surfaces, however when white or pale colours are being applied over a black or dark substrate, a third coat may be necessary.