



**IDEAL
FOR KITCHENS
AND BATHROOMS**

TX 140[®] 2-in-1

ALL-PURPOSE SKIMCOAT FOR FILLING, LEVELLING AND SMOOTHING ON SOFT AND TILED SUBSTRATES



- ▶ **EXCELLENT ADHESION ON ALL SUBSTRATES**
- ▶ **EASY TO SPREAD AND SAND**
- ▶ **REMAINS FLEXIBLE WHEN DRY**
- ▶ **SUITABLE FOR INDOOR/OUTDOOR USE**

PURPOSE

All-purpose filler for filling, levelling and smoothing, dedicated to soft and tiled substrates, interior or exterior, suitable for manual application.

SUBSTRATES

TX 140[®] 2-in-1 can be applied to all painted and unpainted substrates:

- Tiles, ceramics and glass tiles,
- Polystyrene and cork,
- Plaster, gypsum plaster and plasterboard,
- Old painted surfaces,
- Any conventional surface preparation filler,
- Concrete and aerated concrete,
- Cement, breeze blocks, brick and stone.

OVERCOATING

TX 140[®] 2-in-1 may be overcoated by all types of indoor and outdoor paint (except mineral paint) and wall coverings (check with us).

Physical and technical FEATURES

- TX 140[®] 2-in-1:** interior/exterior filler in paste form, made from calcium carbonate and selected resins.
- Characterisation (NFT 36-005): Family IV-4b
 - Coding (EN 16-566): G₃S₂V₁W₂A₀C₀R₀
 - Application thickness: up to 4mm per coat
 - Consumption: approx. 1.6kg/m²/mm
 - Second coat: 12 to 24 hours
 - Overcoating: 24 to 48 hours on average (once completely dry)
 - Colour: cream white
 - Skimcoat/substrate adhesion (EN 16566): > 0.8MPa

Use and storage CONDITIONS

- Application tools: smoothing blade or trowel.
- Cleaning of tools: with water.
- Storage of the skimcoat: product guaranteed for 12 months from the date of purchase, with original purchase receipt as evidence, in its original sealed packaging and kept away from sub-zero temperatures and sunlight.

PACKAGING

- 5kg and 15kg tubs.

RECOMMENDATIONS and precautions for use

- Do not apply at temperatures below 5°C or above 35°C, or at a hygrometry rate over 80%.
- Do not apply on very warm substrates or fully exposed to the sun.
- Do not cover directly with solvent-borne polyurethane or epoxy paints.
- Do not apply on substrates in direct contact with liquid water (run-off, splash, etc.).
- Apply only on vertical substrates.

SURFACE PREPARATION

- Substrates shall be prepared as per current building regulations.
- The surfaces must be hard, cohesive, clean and sound.
- An untreated masonry substrate may be dampened before application.


NORMATIVE DOCUMENTS for reference purposes

- EN 16566: Paints and varnishes. Fillers for internal and/or external works.
- French standard NFT 36-005: characterization of paint products.
- French building regulation DTU 59.1 (NFP 74-201): paintwork for buildings.
- French building regulation DTU 59.4 (NFP 74-204): application of wallpapers and wall coverings.
- French building regulation DTU 42.1 (NFP 84-404): reconditioning of building façades in use with polymer-based waterproof coatings.

HEALTH AND SAFETY

- Product safety data sheets available at toupret.co.uk.

Information on the technical data sheet, and especially the recommendations concerning the application and use of **TX 140[®] 2-in-1**, is provided in good faith, and is based on the knowledge and experience of the company **TOUPRET**. The product must be applied in accordance with the current trade practices and in line with our recommendations. The information provided is relevant for application at a temperature of 20°C, with a hygrometry rate of 50% and on normally-absorbent substrates. The times are provided for information only and depend on the substrate, the thickness of the coat applied and the ambient conditions.



Information about emissions of volatile substances into the indoor air, which may present a toxicity risk through inhalation, on a scale ranging from A+ (very low emissions) to C (high emissions).