

ARBO® Façade Solutions have a market leading portfolio of sealant solutions that work in the modern environment. The range incorporates ARBO® EPDM rolls, one and two part structural silicone sealants, adhesive tapes and expanding strip products. This is an evolving market and we would work with you in developing quality sealing solutions that is fit for your individual project requirements.

Over 160 Years of British Manufacturing Excellence



Total Façade Sealing System:

- We have developed a complete product offer supported by technical field sales professionals, experienced production and administrative teams based in our Head Office in Belper, Derbyshire. We pride ourselves on a high level of product availability and dispatch from our four strategically placed UK distribution centres.

Dedicated R&D:

- In-house research and development facilities from our fully equipped laboratory innovating bespoke products and sealing solutions. The lab also undertakes quality checks and product testing.

SALES & DISTRIBUTION

Andrew Cooper
Façade Product Manager UK

E andrew.cooper@ccm-europe.com
T 07879 521178

DISTRIBUTION CENTRES

BELPER

Derby Road, Belper,
Derbyshire, England,
DE56 1WJ

T 01773 826661
F 01773 821215
E info.arbo@ccm-europe.com

Opening Hours
Mon to Fri
07.00 to 16.30

MANCHESTER

Unit 54,
Oakhill Trading Estate,
Worsley Road North,
Worsley, Manchester
M28 3PT

T 01204 795335
F 01204 862795
E paul.leyland@ccm-europe.com

Opening Hours
Mon to Thu
07.00 to 16.30
Fri
07.00 to 16.00

ESSEX

Unit P1, Pegasus
Works, Hainault
Business Park,
Roebuck Road,
Hainault,
IG6 3UF

T 020 8501 5005
F 020 8500 9830
E raymond.vanson@ccm-europe.com

Opening Hours
Mon to Thu
06.00 to 15.30
Fri
06.00 to 14.30

LONDON

Unit 22, Old Jamaica,
Business Estate,
24 Old Jamaica Road,
London, SE16 4AW

T 0207 3945065
F 0207 3945067
E lawrence.boland@ccm-europe.com

Opening Hours
Mon to Thu
06.30 to 16.00
Fri
06.30 to 14.00

CARLISLE®
Adshead Ratcliffe & Co Ltd.

United Kingdom

Derby Road, Belper,
Derbyshire
DE56 1WJ

T +44 (0)1773 826661
F +44 (0)1773 821215
E info.arbo@ccm-europe.com

www.ccm-europe.com

CUSTOMER SERVICE

DIRECT TELEPHONE LINE:

01773 826661

TECHNICAL SUPPORT

DIRECT TELEPHONE LINE:

01773 596301

ARBO

Façade System

FAÇADE SOLUTION FOR THE GLAZING AND CLADDING INDUSTRY



ARBO® EPDM Membrane System


ARBO® EPDM Membrane System

ARBO® EPDM Membrane System



EPDM ARBO® System:

EPDM system to seal internally and externally between window frames and a variety of substrates using high quality EPDM utilising solvent free adhesives. This green system helps the building achieve Document L. Available in 20 & 25 m reels, in widths from 100mm upto 1400mm, in 50mm increments.



Easy Stick GS: A long lasting 1.3mm EPDM strip, with fibreglass reinforcement, self-adhesive butyl underlay with a split liner. Split liner is positioned 30mm from the edge for ease of application. Available in 100mm to 1000mm (in 50mm increment). Reel length 20m.



Profile EPDM:

ARBO EPDM profile membrane with a bonded extruded rubber strip allows the membrane to be secured in place to the window frame. Also available with extruded rigid PVC black carrier. Available in 100-500 mm width (in 50mm increment). Reel length 20m.



ARBO® Façade Membrane BS-1:

Same quality ARBO® membrane with the addition of one butyl strip for easy application to the frame. Available in 100-500 m m width (in 50mm increment). Reel length 25m.



ARBO® FR-RS FIRE TAPE - BLACK:

ARBO® FIRE TAPE is a high quality elastomeric modified butyl tape. The tape has a B-S1-D0 fire classification and creates an airtight and fire-safe detailing around the window and door frames. For ease of installation it comes with split liner, which is positioned 30mm from the edge. Available in 100mm-1000mm (in 50mm increment). Reel length 10m.



ARBO® MA Adhesive: A one part moisture curing, solvent free adhesive based on modified polymer technology. It combines good initial grab to a variety of common construction substrates with high bond strength and good flexibility. Available in 600ml foils.




ARBO®Bute Al-Band

A laminated tape of butyl and aluminised polyester for sealing glass to glass joints in roofs and curtain walling. Self-wound for easy application. Available in 100 - 300 mm width. 10m roll.



Xpanda 600: A unique combination of resilient foam and a water resisting binder. The combination produces a "dry" pre-formed strip seal used to resist weather ingress in fenestration, roofing and construction applications. The viscoelastic properties also offer noise and vibration damping.



ARBO®SST Tape: A specialised load-bearing PVC foam tape, designed to act as a spacing element between the IG (insulated glass) unit and frame during the assembly of structural glazing fabrications. Available in Roll width of 6mm up to 1200mm.



Ultra-glaze SSG 4000E: A structural glazing adhesive is a one-component, high-strength neutral cure silicone elastomeric adhesive designed and tested for structurally glazed curtain wall applications. The material is supplied as a paste, which cures into a durable flexible silicone rubber upon exposure to atmospheric moisture.



Arbosil 1096: A weatherseal silicone one part low modulus neutral cure sealant which cures on exposure to moisture vapour to form an elastic silicone rubber.



Contact Adhesive: A solvent based contact adhesive, which can be brush or roller applied. Designed to work in conjunction with all ARBO® EPDM Membrane systems. Available in 4.2 kg tin.



AFS Primer: Arbo AFS Primer is a one part, solvent containing, air-drying polyacrylate/silane blend based primer. Recommended for use in conjunction with the Arbo Membrane System for use with Arbo SA and Arbo Membrane Adhesive. Available in 1 Ltr can.



ALUTRIX® 600: Vapour Barrier Membrane

High performance vapour barrier membrane with a self-adhesive backing. Ideal for internal and external (not as a finish) walls subject to very high humidity such as breweries, swimming pools, sports halls, kitchens and bathrooms.



1200 VCL: A high specification, blown polythene material, suitable for use as a vapour control layer within the walls of timber frame constructions, or where control of the passage of water vapour is required. For efficient installation **Double Sided Butyl Tapes** are available.



FR Reflective VCL:

A reflective, airtight and flame resistant membrane with B-S1-D0 rating. It is designed for use as a high performance vapour control layer and air leakage barrier. Suitable for use in any insulated wall or roof application where high moisture vapour resistance is required.



FR Breather: B-S1-D0* fire class breather membrane, dual approved for use in both roof and wall applications.


**when fitted to A1 or A2 materials, D-s2, do on wood materials*



ARBO® Cleaner No.16: An Alcohol based cleaner suitable for the cleaning and degreasing of many different construction products without destroying certain sensitive surfaces. Available in 1L can.



ARBO® Terminator Strip: To mechanically fix and support ARBO® EPDM membranes to a door or a window. It is also recommended for use when large areas of EPDM are being installed and the wet strength of the adhesive is not sufficient to prevent the material from moving whilst the adhesive cures.



ARBO®Internal & External Corners EPDM:

ARBO® EPDM corners are designed for internal and external corner details for difficult applications. Larger size can be specially designed for any project where required.



Accessories: A range of accessories and tools including roller and foil guns, sold separately.