

DuPont™ Tyvek® Trifecta™ Installation

NBS: H92 785, P10 320

Also: H20, H21, H30, H31, M30

Storage

Rolls of Tyvek® Trifecta™ should be stored palletised or on their sides on a smooth clean surface, under cover and protected from direct sunlight.

General

Once a sprayer is selected for use with LiquidArmor™ QS Flashing Care should be taken when handling the membrane in order to prevent tears and punctures occurring. Any that do occur should be repaired with DuPont™ AirGuard® FR System Tape (1310FR).

Application

Unroll Tyvek® Trifecta™ horizontally over the face of the construction. Ensure maximum coverage of membrane by extending 100mm min below the lowest structural timber/steel member.

Fixing – to timber studs/sheathing

Fix Tyvek® Trifecta™ with stainless steel staples or corrosion resistant nails; a rubber or EPDM washer should sit between the screw heads and the membrane to avoid water ingress. Alternatively, fixings can be applied in the overlap section. Fix membrane at 600mm centres horizontally, 300mm centres vertically and at 150mm centres at joints and openings.

Fixing – to masonry

Tyvek® Trifecta™ may be fixed to masonry with a suitable anchor fixing system or a masonry nail/screw and EPDM rubber washer. Fixings should be at maximum 500mm centres. Tyvek® 1310D double sided tape (20mm width) may be used in continuous vertical strips at 1200mm centres to provide complimentary adhesion to the substrate in conjunction with appropriate mechanical fixings

Fixing – to steelwork (SFS)

Tyvek® Trifecta™ can be fixed to Steelwork with an appropriate mechanical fixing through to the steel structure, commonly suitable drill-tip or self-tapping screws may be used. The screws must sit flush (not countersunk) and a rubber or EPDM washer should sit between the screw heads and the membrane to avoid water ingress. Screw fixings should be spaced vertically at 500mm centres on every stud (typically spaced at 600mm horizontal centres).

Fixing – Rainscreen Cladding Applications

Tyvek® Trifecta™ may be fixed to the external face of a cement bonded particle board, external Gypsum board or other Euroclass A1/A2 rated sheathing, using a sheathing appropriate fixing. Appropriate fixings range from stainless Steel Staples for denser boards to drill-tip or self-tapping screws (with soft washers). See Fixing – to steelwork (SFS) above. or Tyvek® double sided tape (1310D) can be used to seal laps at perimeters.

Tyvek® 1310D double sided tape (20mm width) may be used in continuous vertical strips at 1200mm centres to provide complimentary adhesion to the substrate in conjunction with appropriate mechanical fixings

Initial fixings are preferable in the lap line or covered with AirGuard® FR System Tape (1310FR) to protect the membranes integrity.

In many cases, the retrospective fixing of cladding brackets (& insulation) will provide the principle security for the membrane. Care should be taken to ensure these components are fixed tightly over the membrane to avoid water ingress.

Laps

All horizontal laps should be 100mm. Vertical laps should be 150mm min.

External corners

Dress Tyvek® Trifecta™ around external corners ensuring a return of 300mm min. Window openings

For additional information on our product(s) and guidance on how to use them you may wish to refer to our step by step Installation Guide and videos. This and other useful information is on our web site:

<https://www.dupont.co.uk/>

For help with a project please contact the DuPont Building Knowledge Centre. (Contact details can be found at the end of this Installation Sheet). Breather Membrane to EN 13859-2:2014 shall be DuPont Tyvek® Trifecta™ as supplied by DuPont Performance Building Solutions, HERE, 470 Bath Rd, Arno's Vale, Bristol, BS4 3AP. UK Description decrease the amount of labor needed for the job. With faster skinning time than other LiquidArmor Flashing and Sealant products, this allows greater flexibility in installation.

Window openings

Wrap Tyvek® Trifecta™ into window/door openings and seal to frame with Tyvek® Acrylic Tape (2060B), AirGuard® FR System Tape (1310FR) or Tyvek® Window Tape (1310PT) if render is later to be applied. Make good to corners using Tyvek® FlexWrap EZ.

Cavity barriers/trays/flashings

Dress Tyvek® Trifecta™ over cavity barrier/tray/flashing ensuring a minimum lap of 100mm. Seal with AirGuard® FR System Tape (1310FR) or Tyvek® double sided tape (1310D).

Floor junctions

Dress Tyvek® Trifecta™ over intermediate floor zone ensuring a minimum lap of 100mm between sheets. Seal with AirGuard® FR System Tape (1310FR) or Tyvek® double sided tape (1310D).

Airtightness – sealing (optional)

Tyvek® Trifecta™ is airtight. With all laps and penetrations sealed, Tyvek® Trifecta™ will significantly contribute to the overall airtightness of the building.

Seal the laps in Tyvek® Trifecta™ with Seal with AirGuard® FR System Tape (1310FR) or Tyvek® double sided tape (1310D).

Fixing penetrations can be sealed by applying by patching with AirGuard® FR System Tape (1310FR). Complicated penetrations may be sealed using Tyvek® FlexWrap EZ.

Compatibility

Where timber treatments are used care should be taken to ensure they are touch-dry before the installation of the Tyvek® membrane. Retrospective spray applied micro emulsions can also pose significant risk to polymer-based materials such as Tyvek®. Masking the membrane against preservative treatments should be considered.

Temporary exposure period

Tyvek® Trifecta™ may be left exposed for a period not exceeding 12 months, provided that the membrane is adequately secured in accordance with our recommendations. Site conditions and exposure to wind should be assessed to determine whether extra security measures for the membrane are required.

Fire regulations

Tyvek® Trifecta™ has Fire Classification A2-s1,d0* in accordance with EN 13501-1:2007+A1:2009 Care should be taken to determine suitability of this membrane for the intended application, with specific regard to building height and proximity to boundary. Users/specifiers should familiarise themselves with their regional regulatory guidance documents, paying heed to any requirements or variations that may affect the use of this product.

*Over any A1/A2 substrate tested to EN13501-1.

Video installation link: <https://www.dupont.co.uk/resource-center.html?BU=pbs&restyle=video>

DuPont Performance Building Solutions
HERE
470 Bath Road
Amo's Vale
Bristol, UK
BS4 3AP

0117 452 9050

Option 1: Technical (Building Knowledge Centre)

Option 2: General Enquiries

Technical Enquiries: Tyvek.construction@dupont.com



**The DuPont™ Tyvek®
Building Knowledge Center**

- Science you can build on -

www.building.dupont.co.uk

www.energy-efficiency.dupont.com

Recommendations as to methods, use of materials and construction details are based on the experience and current knowledge of DuPont and are given in good faith as a general guide to designers, contractors and manufacturers. This information is not intended to be a substitute for any testing you may need to conduct to determine, for yourself, the suitability of our products for your particular purposes. This information may be subject to revision as new knowledge, regulations and experience becomes available since we cannot anticipate all variations in actual end-use conditions. DuPont makes no warranties and assumes no liability in connection with any use of this information. Nothing in this publication is to be considered as a licence to operate under a recommendation to infringe any patent right.

Tyvek® construction membranes are manufactured by DuPont under an ISO 9001: 2015 Quality Assurance System.

NOTICE: No freedom from any patent owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries or regions. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DUPONT. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. The buyer assumes all risks as to the use of the material. Buyer's exclusive remedy or any claim (including without limitations, negligence, strict liability, or tort) shall be limited to the refund of the purchase price of the material. Failure to strictly adhere to any recommended procedures shall release DuPont Specialty Products USA, LLC or its affiliates, of all liability with respect to the materials or the use thereof. The information herein is not intended for use by non-professional designers, applicators or other persons who do not purchase or utilize this product in the normal course of their business.