

## TECHNICAL DATA SHEET

### HPC 106 / 107 NU-FLAME FR UNDERCOAT / GLOSS

**DESCRIPTION:**

Nu-Flame FR Undercoat and FR Gloss are oil based flame retardant paints for new and previously painted surfaces where a gloss finish is required.

**ADVANTAGES:**

When Nu-Flame FR Undercoat and FR Gloss are used together. They provide a washable weather resistant finish for interior and exterior use.

**Tested to BS 476 part 7 and passes Class 1 surface spread of flame**

**USES:**

For use on door, skirting and other timber finishes.  
To complement the Nu-Flame wall finishes.

**PREPARATION:**

Ensure surfaces to be treated are clean, free from contamination and dry.

**APPLICATION:**

By brush/roller or spray. Should not be applied at temperatures below 5°C, Or when relative humidity exceeds 85%.

**EQUIPMENT CARE:**

All equipment should be cleaned with white spirit.

**STORAGE:**

Store away from direct sunlight and sources of heat.  
Protect from frost.

**SHELF LIFE:**

12 months (in original sealed container).

**HEALTH & SAFETY:**

Refer to MSDS

	HPC 106 Nu-Flame FR Undercoat	HPC 107 Nu-Flame FR Gloss
<b>COLOUR</b>	Any RAL / BS4800 Colour	Any RAL / BS4800 Colour
<b>PACK SIZE</b>	SP 5 Litres	SP 5 Litres
<b>COVERAGE</b>	14 m <sup>2</sup> /litre	14 m <sup>2</sup> /litre
<b>DRYING TIME</b>	4 Hours 16 Hours	4 Hours 12 Hours