

TECHNICAL DATA SHEET – HPC 14 NU-GUARD SB MASONRY

DESCRIPTION:

Nu-Guard SB Masonry Coating is a high performance exterior masonry coating containing a tough synthetic rubber resin, making it first choice for application in cold humid conditions. British Board of Agrément approved product.

ADVANTAGES:

Due to its special drying properties Nu-Guard SB Masonry Coating can be applied all year round, giving protection in excess of 15 years. Rain resistant within 30 minutes of application. May be applied at temperatures as low as -15°C.

USES:

For exterior masonry surfaces including brick, concrete, stone, cement rendering, pebble-dash and asbestos sheeting.

COLOUR RANGE:

Available in selected BS 4800 colour range.

Consult Hydron Technical Services Department.

PACK SIZE:

Single component product, supplied in 5 litres

COVERAGE RATE:

This is dependant upon the surface porosity. Average coverage rate is in the region of 8 – 12 m² per litre.

DRYING TIME:

Touch dry 2-4 hours,. Fully dry 12-24 hours

PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry.

APPLICATION:

Brush, Roller or Airless Spray

EQUIPMENT CARE:

All equipment should be cleaned with Nu-Guard SB Brush Cleaner.

STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS