

TECHNICAL DATA SHEET – HPC 124 NU-BASE WB CLEAR SEAL

DESCRIPTION:

Nu-Base WB Clear Seal is a two-pack water based epoxy resin. For sealing concrete, or for where a primer is required prior to the application of Nu-Base WB or HB Epoxy Finish.

ADVANTAGES:

Nu-Base WB Clear Seal has good chemical resistance. Will not support fungus or bacterial growth and is therefore suitable for application in food production areas, hospitals etc.

USES: FeRFA Class Type 1

Nu-Base WB Clear Seal is suitable for use in garages, workshops and general industrial usage.

COLOUR:

Clear

COVERAGE RATE:

7-8 m² / KG

DRYING TIMES

Touch dry	8 hours @ 20°C.
Overcoat	24 hours.
Full Cure	7 days.

POT LIFE:

1 – 1.5 Hours @ 20°C

VOLUME SOLIDS:

50 %

VOC CONTENT:

<1g/L. Calculation based on a full mixed unit.

PACK SIZE

Two component product, supplied in 5 & 10 KG units.

PREPARATION:

All surfaces to be coated should be clean, dry and free from oil and grease etc. Ideally the substrate should be shot-blasted, mechanically abraded or acid etched with all loose, flaking materials and any laitance removed.

APPLICATION:

By brush/roller or airless spray

EQUIPMENT CARE:

All equipment should be cleaned with water immediately after use.

STORAGE:

Recommended storage is in a cool, dry place with temperatures between 10-15°C, and in accordance with the Highly Flammable Liquids and Liquefied Petroleum Gases Regulations 1972.

SHELF LIFE:

12 months (in original sealed container).

HEALTH & SAFETY:

Refer to MSDS