

## TECHNICAL DATA SHEET – NU-STEEL CLADDING PAINT

### DESCRIPTION:

Nu-Steel Cladding Paint is a single pack, modified acrylic paint specifically developed for application to Plastisol and polyester coated steel and aluminium cladding.

### ADVANTAGES:

Will provide excellent resistance to UV attack

### USES:

For use on properly prepared cladding and prefabricated buildings, architectural steelwork, and industrial environments.

### PREPARATION:

Ensure surfaces to be treated are clean, free from contamination and dry. Degrease plastisol with MC1 Multiclean and rinse down with clean water. Allow to dry.

### APPLICATION:

By brush/roller or Airless Spray

### EQUIPMENT CARE:

All equipment should be cleaned with T5 Thinners.

### STORAGE:

Store away from direct sunlight and sources of heat. Protect from frost.

### SHELF LIFE:

12 months (in original sealed container).

### HEALTH & SAFETY:

Refer to MSDS

	HPC 61 Cladding Primer	HPC 62 Cladding Finish
<b>COLOUR</b>	White/Grey	Any RAL / BS4800 Colour
<b>PACK SIZE</b>	S.P 5 Litres	S.P 5 Litres
<b>COVERAGE</b>	8 m <sup>2</sup> /litre	6 m <sup>2</sup> /litre
<b>DRYING TIME</b>	4 Hours 8 Hours	3 Hours 24 Hours