

Technical Data – Wall Seal

(90.41) E (G)

PRODUCT DESCRIPTION

Wall Seal is a pre-mixed, colourless blend of high-grade acrylic resin polymers and aromatic solvents.

PURPOSE

To impregnate Wallcrete and give benefits of hardening, dust proofing, sealing and colour enhancing.

SPECIAL PROPERTIES

- Seals Wallcrete
- Special blend of polymers do not soften in hot temperatures nor become brittle in freezing conditions
- Low viscosity ensures full penetration into the dense surface matrix creating a true in-surface seal (ISS)
- Non-reemulsifiable, non-blooming when wet
- 100% inter-coat adhesion
- Non-yellowing
- Mechanical bond with surface matrix prevents delamination
- Tough, durable and hard wearing
- Designed for use with Wallcrete to enhance the full depth of colour and Wallstain highlights

APPLICATION INSTRUCTIONS

Surface must be clean and dry. Wall Seal can be applied by brush or sprayed with a Viton equipped sprayer. Apply in 2-3 light coats to avoid dripping down the wall in order to achieve a uniform low sheen.

APPROXIMATE COVERAGE

3-5 m² per litre

STORAGE

Store in a cool, dry place.

PACKAGING

5 and 25 litre U.N. 1993 approved drums.

HEALTH AND SAFETY

Flammable liquid. Do not smoke. Keep application area well ventilated. Wear respirator when applying. Store in a cool place. Flash point 42°C (Abel-Closed Cup). Refer to the Health & Safety Data Sheet for further information.

TECHNICAL SERVICES

For further information, call our technical dept on:-

Φ UK

(01635) 202224

Φ International

+44(0) 1635 202224

e-mail

info@picsuk.com

Web Site

www.picsuk.com

29-11-2023

Warranty

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice,

Manufactured by:

PATTERN IMPRINTED CONCRETE SUPPLIES LIMITED
Unit 2 & 4, Red Shute Hill Ind. Est., Hermitage,
Nr Newbury, Berkshire, RG18 9QL, United Kingdom
www.picsuk.com
info@picsuk.com

