

## Technical Data – Permaseal SF

### PRODUCT DESCRIPTION

**Permaseal Solvent Free (SF)** Is a clear, UV light-stable solution designed to penetrate and stabilise the jointing sand of block paving and pre-cast flagstones to inhibit the growth of weeds and moss and reduce sand loss. **Permaseal SF** will also seal the paving to enhance the appearance whilst facilitating the easy removal of oil and other stains.

### PURPOSE

**Permaseal SF** has been designed to protect jointing sand from erosion thus reducing movement and weed infestation in block paved surfaces. In addition it can improve the aesthetic appearance of blocks, paving slabs and other cementitious substrates and increase abrasion resistance.

### SPECIAL PROPERTIES

- Reduces sand loss from joints
- Reduces efflorescence
- Ultra-violet light and weather resistant
- Inhibits the growth of moss and weeds
- Excellent resistance to water whitening
- Enhances the colour of the paving
- Facilitates the easy removal of oil and other contamination
- Will not blister or peel

### APPLICATION INSTRUCTIONS

**Permaseal SF** should be used in dry weather when rain is not forecast. **Permaseal SF** can be applied using spray and squeegee at a rate of 3m<sup>2</sup> per litre to an easily managed area not exceeding 10m<sup>2</sup> at any one time. In the event that two applications are required the second application must be applied prior to the first application becoming tack-free.

**Permaseal SF** will be tack-free after two hours at 20°C and foot traffic may be permitted after 12 hours. Vehicles should be kept off the treated area for a minimum of 24 hours and 20°C. These times may be increased or reduced depending on the ambient temperature. During the drying cycle protect from rain. Do not apply when the ground temperature is above 30°C or below 5°C. Clean all equipment after use with clean water.

### PREPERATION INSTRUCTIONS

New block or flagstone paving should be swept clean, ensuring there is sufficient well-compacted sand in the joints. Existing paving should be pressure washed to remove all surface debris. If the area is contaminated with weeds & moss then it should be treated with **PICS Fungicidal wash**.

Oil & other stains should be removed using **PICS Clean** degreaser. The treated area should then be left to dry & the joints re-sanded & compacted to the lower edge of the paver chamfers with clean kiln-dried sand. Moisture in the paver & sand will inhibit penetration of the sealer and produce whiteness.

### TECHNICAL & TEST DATA

**Permaseal SF** has been tested for chemical resistance by one hour exposure to a range of substances, including used motor oil, deionised water, 10% sodium hydroxide, sodium chloride, calcium chloride, trisodium phosphate, ammonia and hydrochloric acid, all with no effect. **Permaseal SF** is supplied in 25 litre U.N. approved drums and covers approximately 3m<sup>2</sup> per litre – in one or two applications, depending on the paving porosity and joint size.

### SPECIFICATION CLAUSE

*“Newly laid block or flagstone paving shall be treated with **Permaseal SF** from PICS (Tel. 01635 202224) to protect and stabilise jointing sand and enhance surface colour and increase abrasion resistance. All materials should comply to ISO9002 for Quality Assurance. All work should be carried out in conjunction with the manufacture’s current technical data sheet and instructions for use”.*

### HEALTH AND SAFETY

**Permaseal SF** in non-toxic and non-flammable. Avoid contact with skin and eyes. Flush affected areas with water. Do not take internally. Refer to Safety data sheet for further information.

### TECHNICAL SERVICES

For further information, call our technical dept on:-  
☎ UK (01635) 202224

☎ International +44(0)1635 202224

e-mail  
Website

info@picsuk.com  
www.picsuk.com

22-08-2023

### Warranty

Pattern Imprinted Concrete Supplies Ltd products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and conditions of Sale, copies of which may be obtained on request. Whilst Pattern Imprinted Concrete Supplies Ltd endeavours to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it cannot, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

Manufactured by:

**PATTERN IMPRINTED CONCRETE SUPPLIES LIMITED**  
Unit 2 & 4, Red Shute Hill Ind. Est., Hermitage,  
Nr Newbury, Berkshire, RG18 9QL, United Kingdom  
www.picsuk.com  
info@picsuk.com

