

# Technical Data – Rhino-Grip Anti Skid Additive

(90.41) E (G)

## PRODUCT DESCRIPTION

**PICS Rhino Grip** is a finely ground and carefully graded micronised white powder which when added to PICS sealers will dramatically improve the Slip Resistance value of all concrete surfaces.

## PURPOSE

**PICS Rhino Grip** is used to increase the Slip Resistance value on concrete surfaces. Typically used on inclined driveways, pathways, steps, patio's and swimming pool surrounds.

## SPECIAL PROPERTIES

- Guaranteed increase in Slip Resistance value
- Effective Cost
- Careful grading ensures even distribution
- No dangerous sharp edges
- Transparent when applied
- Can be used on all re-seals

## APPLICATION INSTRUCTIONS

Add the contents of the container to 25 lts of **PICS High Solids Sealer (CM41)** and mix well.

Ensure the **Rhino Grip** is evenly dispersed through the 25 lts of **High Solids Sealer (CM41)**.

Apply to the clean dry surface using a natural fibre brush.

Agitate every 20 minutes to avoid settlement.

For **Low Solids Sealer (CM42)** a second spray applied application (without **Rhino-Grip**) may be required depending on porosity of the surface.

**For more detailed information please refer to the PICS Application Instruction Sheet.**

01-02-2000

## TECHNICAL & TEST DATA

<b>PACKAGE:</b>	0.5kgs Plastic Tub
<b>YIELD:</b>	1 tub per 25 lts
<b>STORAGE:</b>	Indefinite
<b>WATER SOLUBILITY:</b>	Insoluble
<b>XYLENE SOLUBILITY:</b>	Insoluble
<b>ODOUR:</b>	None
<b>BIOLOGICAL RESISTANCE:</b>	Good/Non Biodegradable

## HEALTH AND SAFETY

**PICS Rhino Grip** is non toxic . Do not take internally. Avoid contact with eyes. Flush effected areas with water.

Refer to the Health & Safety Data Sheet for further information.

As this product is intended for use with either **High** or **Low Solids Sealer** please also consult the appropriate sealer Health & Safety Data Sheet.

## TECHNICAL SERVICES

For further information, call our technical dept on:-  
☎ UK (01635) 202224

☎ FAX (01635) 202230

☎ International +44(0) 1635 202224

☎ Fax International +44(0) 1635 202230

e-mail  
Web Site

[info@picsuk.com](mailto:info@picsuk.com)  
[www.picsuk.com](http://www.picsuk.com)