



# HATCRETE Sealers



**TECHNICAL DATA**  
**TD25**

**COLOUR TECHNOLOGY FOR CONCRETE**

### **HATCRETE® Sealer (solvent based)**

The designated surface shall be cured and (delete if inappropriate) sealed with 2 coats of HATCRETE® ..... at a rate of 6-10 square metres per litre, per coat, as supplied by PICS Ltd Unit 2, Red Shute Hill Ind. Est. Hermitage, Nr Newbury, Berkshire RG18 9QL Tel: +44 (0) 1635 202224 Fax: +44 (0) 1635 202230. The sealer should be applied by airless sprayer and all work should be carried out in accordance with the manufacturer's current technical data sheet and with reference to the specific health & safety information. The manufacturer shall be a BSI registered company with accreditation to BS EN ISO 9002.

### **HATCRETE® Sealer (water based)**

The designated surface shall be cured and (delete if inappropriate) sealed with 2 coats of HATCRETE® .....at a rate of 6-10 square metres per litre, per coat, as supplied by PICS Ltd Unit 2, Red Shute Hill Ind. Est. Hermitage, Nr Newbury, Berkshire RG18 9QL Tel: +44 (0) 1635 202224 Fax: +44 (0) 1635 202230. The sealer should be applied by airless sprayer and all work should be carried out in accordance with the manufacturer's current technical data sheet and with reference to the specific health & safety information. The manufacturer shall be a BSI registered company with accreditation to BS EN ISO 9002.



**MANUFACTURED BY:**

**PATTERN IMPRINTED CONCRETE SUPPLIES LIMITED**

**Unit 2, Red Shute Hill Ind. Est. Hermitage, Nr Newbury, Berkshire RG18 9QL**

**Tel: +44 (0) 1635 202224 Fax: +44 (0) 1635 202230 e-mail: info@picsuk.com Web: www.picsuk.com**